

**BOTO**

中国万达集团  
CHINA WANDA GROUP



Xiamén Business Corporation  
E- mail Sales@xiamenbusiness.com

**BOTO**

**TBR TYRE  
BROCHURE  
2024**



**BOTO**

XIAMEN BUSINESS CORPORATION  
E-mail: [saies@xiamenbusinees.com](mailto:saies@xiamenbusinees.com)





### Introduction to China Wanda Group

Located in the beautiful Yellow River Estuary and the cradle of Shengli Oil field,Dongying, Shandong, China Wanda Group was founded in 1988. China Wanda Group is entering a new development stage after passing its three-step-development of advancing by science and technology, creating advantage by brand building and developing through cooperation while holding its vision of gathering scientific and technological talents and building up Wanda foundation evergreen.During 30 years development, Wanda Group experienced its initial development phase of “Advancing by Science and Technology, Creating Advantage by Branding Building and Developing through Cooperation” . The group has formed its industrial pattern of “Science and Technology Playing a Leading Role in Development,Integrating Petrochemical and Rubber Industry and Developing Diversified Business” and developed to become a large scale enterprise group with its business covering petrochemical, tires, sea terminal logistics and finance and trade etc. The group owns over 80 billion yuan total assets, covers an area of 60 billion square meters and employs over 13,000 staff and workers The group is authorized to carry out crude oil importation and refined oil product wholesale. The group is also qualified for opening of its sea terminals to public service and outbound construction contract project. Wanda group has won many honorable titles like National May 1st Labor Award, National Contract-respect Enterprise,AAAA Class Enterprise with National Standardized Good Behaviour. The group is only one private enterprises whose parent company and its subsidiary company are evaluated AA+ Credit in Shandong Province.



### Introduction to Shandong Wanda Boto Tyre Co.LTD

Shandong Wanda Boto Tyre Co.LTD is one of the large enterprises in China that specializes in manufacturing TBR, OTR, PCR and light truck tires.The company employees over 3600 staff among which more than 30% are granted with colleague degree or above. Located in the beautiful Yellow river estuary-Dongying, the company is a wholly-owned subsidiary of China Wanda Group, which is one of Top 500 national industrial enterprises in economic strength. Shangdong Wanda BOTO tyre Co., Ltd is a large scale of professional tire production enterprise and China Quality and Credit enterprise. Shangdong Wanda BOTO tyre Co., Ltd sincerely welcomes friendsfrom home and abroad for export business discussion!





## BT118



- ▶ Mainly for drive axle, also applicable for steer wheel
- ▶ Special pattern design, only applicable to driving on mining and bad roads with low speed
- ▶ Excellent grip and ride ability performance
- ▶ The pattern is good in self-cleaning, superior for wear and puncture resistance

SIZE	PR	NEW TYRE INFLATED DIMENSIONS(mm)		LOAD INDEX	MAX.LOAD (kg)		PRESSURE		SPEED RATING	STANDARD RIM	TREAD DEPTH (mm)
		SECTION WIDTH	OVERALL DIAMETER		SINGLE/DUAL	SINGLE/DUAL (kg)	SINGLE/DUAL (kpa)				
10.00R20	16PR	278	1054	146/143	3000/2725	830/830	F	7.5	21		
10.00R20	18PR	278	1054	149/146	3250/3000	930/930	F	7.5	21		
10.00R20	18PR	278	1054	149/146	3250/3000	930/930	K	7.5	21		
11.00R20	16PR	293	1085	150/147	3350/3075	830/830	F	8.0	22		
11.00R20	18PR	293	1085	152/149	3550/3250	930/930	F	8.0	22		
12.00R20	18PR	315	1125	154/151	3750/3450	830/830	F	8.5	22		
12.00R20	20PR	315	1125	156/153	4000/3650	900/900	F	8.5	22		



## BT151



- ▶ Aggressive lug tread for powerful grip on or off the road.
- ▶ Deep original tread for long life and outstanding traction.
- ▶ Special tread compounds help resist cuts, chips, tearing and irregular wear

SIZE	PR	NEW TYRE INFLATED DIMENSIONS(mm)		LOAD INDEX	MAX.LOAD (kg)		PRESSURE		SPEED RATING	STANDARD RIM	TREAD DEPTH (mm)
		SECTION WIDTH	OVERALL DIAMETER		SINGLE/DUAL	SINGLE/DUAL (kg)	SINGLE/DUAL (kpa)				
11.00R20	18PR	293	1085	152/149	3550/3250	930/930	J	8.0	20		
12.00R20	20PR	315	1125	156/153	4000/3650	900/900	J	8.5	20.5		
12R22.5	18PR	300	1085	152/149	3550/3250	930/930	K	9.00	20		
12R22.5	20PR	320	1124	156/153	4000/3650	930/930	K	9.75	20		



## BT128



- ▶ Mainly for drive axle on mining and bad roads with low speed
- ▶ Excellent traction with big block pattern design
- ▶ Special compound supply anti crack and anti puncture performance
- ▶ Good performance on carrying capacity

SIZE	PR	NEW TYRE INFLATED DIMENSIONS(mm)		LOAD INDEX	MAX.LOAD (kg)		PRESSURE		SPEED RATING	STANDARD RIM	TREAD DEPTH (mm)
		SECTION WIDTH	OVERALL DIAMETER		SINGLE/DUAL	SINGLE/DUAL (kg)	SINGLE/DUAL (kpa)				
9.00R20	16PR	259	1054	146/143	3000/2725	830/830	F	7.5	21		
9.00R20	16PR	259	1054	149/146	3250/3000	930/930	F	7.5	21		
10.00R20	16PR	278	1054	149/146	3250/3000	930/930	K	7.5	21		
10.00R20	18PR	278	1085	150/147	3350/3075	830/830	F	8.0	22		
11.00R20	16PR	293	1085	152/149	3550/3250	930/930	F	8.0	22		
11.00R20	18PR	293	1125	154/151	3750/3450	830/830	F	8.5	22		
12.00R20	20PR	315	1125	156/153	4000/3650	900/900	F	8.5	22		



## BT156



- ▶ Mainly for drive and trailer axle
- ▶ On-off highway application
- ▶ Excellent traction and brake performance
- ▶ Good carrying capacity and low heating up

SIZE	PR	NEW TYRE INFLATED DIMENSIONS(mm)		LOAD INDEX	MAX.LOAD (kg)		PRESSURE		SPEED RATING	STANDARD RIM	TREAD DEPTH (mm)
		SECTION WIDTH	OVERALL DIAMETER		SINGLE/DUAL	SINGLE/DUAL (kg)	SINGLE/DUAL (kpa)				
325/95R24	22PR	325	1228	162/160	4750/4500	850/850	K	9.0	19.5		



## BT157



- ▶ Drive wheel application
- ▶ Mainly for regional and medium haul on mixed road condition
- ▶ Directed and mixed pattern with strengthening rib for good drive and brake performance
- ▶ Deep tread to extend tire service life
- ▶ Improved carcass in structure design for good carrying capacity

SIZE	PR	NEW TYRE INFLATED DIMENSIONS(mm)		LOAD INDEX	MAX.LOAD (kg)	PRESSURE	SPEED RATING	STANDARD RIM	TREAD DEPTH (mm)
		SECTION WIDTH	OVERALL DIAMETER						
10.00R20	18PR	278	1054	149/146	3250/3000	930/930	K	7.5	19
12.00R24	18PR	315	1226	158/155	4250/3875	830/830	J	8.5	19
12.00R24	20PR	315	1226	160/157	4500/4125	900/900	K	8.5	19
325/95R24	22PR	325	1228	162/160	4750/4500	850/850	K	9.0	19.5



## BT168



- ▶ All position axls
- ▶ For regional application on various road

SIZE	PR	NEW TYRE INFLATED DIMENSIONS(mm)		LOAD INDEX	MAX.LOAD (kg)	PRESSURE	SPEED RATING	STANDARD RIM	TREAD DEPTH (mm)
		SECTION WIDTH	OVERALL DIAMETER						
7.50R16LT	12PR	215	805	120/116	1400/1250	670/670	L	6.00G	12
7.50R16LT	14PR	215	805	122/118	1500/1320	770/770	L	6.00G	12
7.50R16LT	16PR	215	805	124/120	1600/1405	800/800	K	6.00G	12
7.50R16LT	16PR	215	805	124/120	1600/1405	800/800	L	6.00G	12
8.25R16LT	14PR	235	855	126/122	1700/1500	670/670	L	6.50H	12
8.25R16LT	16PR	235	855	128/124	1800/1600	770/770	K	6.50H	12
8.25R16LT	16PR	235	855	128/124	1800/1600	770/770	L	6.50H	12
7.50R20	12PR	215	935	128/126	1800/1700	760/760	L	6.0	
7.50R20	14PR	215	935	130/128	1900/1800	830/830	K	6.0	
8.25R20	12PR	236	974	133/131	2060/1950	720/720	L	6.5	13.5
8.25R20	14PR	236	974	136/134	2240/2120	830/830	K	6.5	13.5
8.25R20	16PR	236	974	139/137	2430/2300	930/930	K	6.5	13.5
9.00R20	14PR	259	1019	141/139	2575/2430	790/790	L	7.0	15.5
9.00R20	16PR	259	1019	144/142	2800/2650	900/900	K	7.0	15.5
10.00R20	16PR	278	1054	146/143	3000/2725	830/830	L	7.5	16.5
10.00R20	16PR	278	1054	146/142	3000/2630	840/770	L	7.5	16.5
10.00R20	18PR	278	1054	149/146	3250/3000	930/930	K	7.5	16.5
11.00R20	16PR	293	1085	150/147	3350/3075	830/830	L	8.0	17
11.00R20	18PR	293	1085	152/149	3550/3250	930/930	K	8.0	17
12.00R20	18PR	315	1125	154/151	3750/3450	830/830	L	8.5	15
12.00R20	20PR	315	1125	156/153	4000/3650	900/900	K	8.5	15
12.00R24	18PR	315	1226	158/155	4250/3875	830/830	J	8.5	17
12.00R24	20PR	315	1226	160/157	4500/4125	900/900	J	8.5	17
12.00R24	20PR	315	1226	160/157	4500/4125	900/900	K	8.5	17
11R22.5	14PR	279	1054	144/142	2800/2650	720/720	M	8.25	16
11R22.5	16PR	279	1054	146/143	3000/2725	830/830	M	8.25	16
11R22.5	16PR	279	1050	148/145	3150/2900	850/850	M	8.25	16
12R22.5	14PR	300	1085	146/143	3000/2725	720/720	L	9.00	17.5
12R22.5	16PR	300	1085	150/147	3350/3075	830/830	L	9.00	17.5
12R22.5	18PR	300	1085	152/149	3550/3250	930/930	L	9.00	17.5
12R22.5	18PR	300	1085	152/149	3550/3250	930/930	L	9.00	17.5
12R22.5	16PR	320	1124	152/149	3550/3250	760/760	M	9.75	17.5
12R22.5	18PR	320	1124	154/151	3750/3450	830/830	M	9.75	17.5
12R22.5	18PR	320	1124	156/150	4000/3350	875/875	L	9.75	17.5
12R22.5	18PR	320	1124	156/150	4000/3350	875/875	K	9.75	17.5
12R22.5	20PR	320	1124	156/153	4000/3650	930/930	K	9.75	17.5
315/80R22.5	18PR	312	1076	154/151	3750/3450	830/830	M	9.00	15
315/80R22.5	20PR	312	1076	157/154	4125/3750	900/900	K	9.00	15
315/80R22.5	20PR	312	1076	156/150	4000/3350	850/850	L	9.00	15
315/80R22.5	20PR	312	1076	156/150	4000/3350	850/850	M	9.00	15



## BT168A



- ▶ All position axls
- ▶ For regional application on various road

SIZE	PR	NEW TYRE INFLATED DIMENSIONS(mm)		LOAD INDEX	MAX.LOAD (kg)	PRESSURE	SPEED RATING	STANDARD RIM	TREAD DEPTH (mm)
		SECTION WIDTH	OVERALL DIAMETER						
12.00R24	18PR	315	1226	158/155	4250/3875	830/830	J	8.5	15
12.00R24	20PR	315	1226	160/157	4500/4125	900/900	J	8.5	15
12.00R24	20PR	315	1226	160/157	4500/4125	900/900	K	8.5	15



## BT188



- ▶ Mainly for drive axle on mix and bad road , such as construction road
- ▶ With good grip performance

SIZE	PR	NEW TYRE INFLATED DIMENSIONS(mm)		LOAD INDEX	MAX.LOAD (kg)	PRESSURE	SPEED RATING	STANDARD RIM	TREAD DEPTH (mm)
		SECTION WIDTH	OVERALL DIAMETER						
9.00R20	14PR	259	1019	141/139	2575/2430	790/790	K	7.0	17.5
9.00R20	16PR	259	1019	144/142	2800/2650	900/900	K	7.0	17.5
10.00R20	16PR	278	1054	146/143	3000/2725	830/830	G	7.5	19.5
10.00R20	18PR	278	1054	149/146	3250/3000	930/930	G	7.5	19.5
11.00R20	16PR	293	1085	150/147	3350/3075	830/830	F	8.0	22
11.00R20	18PR	293	1085	152/149	3550/3250	930/930	F	8.0	22
12.00R20	18PR	315	1125	154/151	3750/3450	830/830	F	8.5	22
12.00R20	20PR	315	1125	156/153	4000/3650	900/900	F	8.5	22
11R22.5	14PR	279	1054	144/142	2800/2650	720/720	G	8.25	24.5
11R22.5	16PR	279	1054	146/143	3000/2725	830/830	G	8.25	24.5
11R24.5	14PR	279	1104	146/143	3000/2725	720/720	G	8.25	24.5
11R24.5	16PR	279	1104	149/146	3250/3000	830/830	G	8.25	24.5
12R22.5	18PR	320	1124	154/151	3750/3450	830/830	F	9.75	
12R22.5	16PR	320	1124	156/150	4000/3350	875/875	G	9.75	
12R22.5	18PR	320	1124	156/150	4000/3350	875/875	K	9.75	



## BT216



- ▶ Mainly for long haul application of light truck and all position wheels on good road
- ▶ For longitudinal grooves design exactly accords with quick movement feature of light truck
- ▶ Low heating up compound ensures good wear resistance and fuel saving
- ▶ Continuous pattern in shoulder avoids tire irregular wear

SIZE	PR	NEW TYRE INFLATED DIMENSIONS(mm)		LOAD INDEX	MAX.LOAD (kg)	PRESSURE	SPEED RATING	STANDARD RIM	TREAD DEPTH (mm)
		SECTION WIDTH	OVERALL DIAMETER						
7.50R16LT	12PR	215	805	120/116	1400/1250	670/670	L	6.00G	12
7.50R16LT	14PR	215	805	122/118	1500/1320	770/770	L	6.00G	12
7.50R16LT	16PR	215	805	124/120	1600/1405	800/800	K	6.00G	12
7.50R16LT	16PR	215	805	124/120	1600/1405	800/800	L	6.00G	12



## BT212/BT212N



- ▶ Mainly for rated load and long haul application for all position wheels. Especially for steer and trailer wheels
- ▶ Applicable for good road at high speed
- ▶ Four straight grooves design offer excellent handing and water drainage performance
- ▶ With cross sipe design to generate a good grip and low heating up performance

SIZE	PR	NEW TYRE INFLATED DIMENSIONS(mm)		LOAD INDEX	MAX.LOAD (kg)	PRESSURE	SPEED RATING	STANDARD RIM	TREAD DEPTH (mm)
		SECTION WIDTH	OVERALL DIAMETER						
11R22.5	14PR	279	1054	144/142	2800/2650	720/720	M	8.25	14
11R22.5	14PR	279	1054	144/142	2800/2650	720/720	M	8.25	14
11R22.5	16PR	279	1054	146/143	3000/2725	830/830	M	8.25	14
11R22.5	16PR	279	1054	146/143	3000/2725	830/830	M	8.25	14
11R22.5	16PR	279	1054	146/143	3000/2725	830/830	L	8.25	14
11R24.5	14PR	279	1104	146/143	3000/2725	720/720	M	8.25	14
11R24.5	14PR	279	1104	146/143	3000/2725	720/720	M	8.25	14
11R24.5	16PR	279	1104	149/146	3250/3000	830/830	L	8.25	14
11R24.5	16PR	279	1104	149/146	3250/3000	830/830	L	8.25	14
12R22.5	18PR	300	1085	152/149	3550/3250	930/930	L	9.00	17.5
12R22.5	18PR	300	1085	152/149	3550/3250	930/930	L	9.00	17.5
255/70R22.5	14PR	255	930	136/133	2240/2060	700/700	M	7.50	14
255/70R22.5	16PR	255	930	140/137	2500/2300	800/800	M	7.50	14
255/70R22.5	16PR	255	930	140/137	2500/2300	830/830	M	7.50	14
255/70R22.5	16PR	255	930	140/137	2500/2300	830/830	M	7.50	14
285/75R24.5	14PR	283	1050	144/141	2800/2575	760/760	M	8.25	14
285/75R24.5	14PR	283	1050	144/141	2800/2575	760/760	M	8.25	14
285/75R24.5	16PR	283	1050	147/144	3075/2800	830/830	L	8.25	14
285/75R24.5	16PR	283	1050	147/144	3075/2800	830/830	L	8.25	14
295/75R22.5	14PR	298	1014	144/141	2800/2575	760/760	M	9.00	14
295/75R22.5	14PR	298	1014	144/141	2800/2575	760/760	M	9.00	14
295/75R22.5	16PR	298	1014	146/143	3000/2725	830/830	L	9.00	14
295/75R22.5	16PR	298	1014	146/143	3000/2725	830/830	L	9.00	14



## BT217



- ▶ Mainly for long haul application and all position wheels on paved road
- ▶ Optimized grooves offer good handling performance –
- ▶ Optimized stone rejecter sipping help prevent retention of damaging stones.

SIZE	PR	NEW TYRE INFLATED DIMENSIONS(mm)		LOAD INDEX	MAX.LOAD (kg)	PRESSURE	SPEED RATING	STANDARD RIM	TREAD DEPTH (mm)
		SECTION WIDTH	OVERALL DIAMETER						
6.50R16LT	12PR	185	750	110/105	1060/925	670/670	L	5.50F	12
7.00R16LT	8PR	200	775	107/102	975/850	460/460	L	5.50F	13
7.00R16LT	12PR	200	775	115/110	1215/1060	670/670	M	5.50F	13
7.00R16LT	14PR	200	775	118/114	1320/1180	770/770	L	5.50F	13



## BT218



- ▶ Mainly for long haul of steer and trailer wheels
- ▶ Cold-running Tyre
- ▶ Applicable to ride on good road and highway

SIZE	PR	NEW TYRE INFLATED DIMENSIONS(mm)		LOAD INDEX	MAX.LOAD (kg)	PRESSURE	SPEED RATING	STANDARD RIM	TREAD DEPTH (mm)
		SECTION WIDTH	OVERALL DIAMETER						
11R22.5	14PR	279	1054	144/142	2800/2650	720/720	M	8.25	14.8
11R22.5	16PR	279	1054	146/143	3000/2725	830/830	M	8.25	14.8
11R22.5	16PR	279	1050	148/145	3150/2900	850/850	M	8.25	14.8
11R24.5	14PR	279	1104	146/143	3000/2725	720/720	M	8.25	14.8
11R24.5	16PR	279	1104	149/146	3250/3000	830/830	L	8.25	14.8
12R22.5	14PR	300	1085	146/143	3000/2725	720/720	M	9.00	14.8
12R22.5	16PR	300	1085	150/147	3350/3075	830/830	L	9.00	14.8
12R22.5		300	1084	152/148	3550/3150	850/850	M	9.00	14.8
12R22.5	18PR	300	1085	152/149	3550/3250	930/930	L	9.00	14.8



## BT215



## BT215N

## BT215/BT215N



- ▶ Long haul application of trailers
- ▶ For high speed riding on good roads
- ▶ Straight main slots design enhances handling performance and service life
- ▶ With high irregular wear resistance technology

SIZE	PR	NEW TYRE INFLATED DIMENSIONS(mm)		LOAD INDEX	MAX.LOAD (kg)	PRESSURE	SPEED RATING	STANDARD RIM	TREAD DEPTH (mm)
		SECTION WIDTH	OVERALL DIAMETER						
LT235/85R16	12PR	235	806	123/120	1550/1400	660/660	M	6.50	9.5
LT235/85R16	14PR	235	806	126/123	1700/1550	760/760	M	6.50	9.5
ST235/85R16	14PR	235	806	129/125	1850/1650	760/760	L	6.50	9.5
ST235/85R16	14PR	235	806	132/127	2000/1750	760/760	L	6.50	9.5
275/70R22.5	14PR	276	958	142/139	2650/2430	760/760	K	8.25	19.2
275/70R22.5	16PR	276	958	144/141	2800/2575	830/830	K	8.25	19.2
275/70R22.5	18PR	276	958	146/143	3000/2725	900/900	J	8.25	19.2
275/70R22.5	18PR	276	958	148/145	3150/2900	900/900	J	8.25	19.2
275/70R22.5	16PR	276	958	148/145	3150/2900	900/900	M	8.25	19.2
385/65R22.5	18PR	386	996	158	4250	850	L	12.25	15
385/65R22.5	18PR	386	996	158	4250	830	L	12.25	15
385/65R22.5	20PR	386	996	160	4500	900	K	12.25	15
385/65R22.5	18PR	389	1072	158	4250	830	L	11.75	15
385/65R22.5	20PR	389	1072	160	4500	900	K	11.75	15
385/65R22.5	20PR	389	1072	164	5000	900	K	11.75	15
425/65R22.5	18PR	422	1124	162	4750	760	L	12.25	15
425/65R22.5	20PR	422	1124	164	5000	830	K	12.25	15
425/65R22.5	22PR	422	1124	166	5300	900	J	12.25	15
425/65R22.5	20PR	430	1124	165	5150	825	K	12.25	15
435/50R19.5	18PR	438	931	156	4000	850	K	14.00	14
435/50R19.5	20PR	438	931	160	4500	900	J	14.00	14
ST225/90R16	14PR	220	808	128/124	1800/1600	830/830	K	6.50	12
ST235/80R16	14PR	235	782	128/124	1800/1600	725/725	L	6.50	9.5
245/70R17.5	16PR	248	789	132/130	2000/1900	830/830	M	7.50	13.5
245/70R17.5	18PR	248	789	134/132	2120/2000	900/900	L	7.50	13.5



## BT267



- ▶ For all position wheels
- ▶ Applicable for regional and long haul on paved road
- ▶ With excellent grip and traction ,anti-skidding performance low noise; better fuel efficiency

SIZE	PR	NEW TYRE INFLATED DIMENSIONS(mm)		LOAD INDEX	MAX.LOAD (kg)	PRESSURE	SPEED RATING	STANDARD RIM	TREAD DEPTH (mm)
		SECTION WIDTH	OVERALL DIAMETER						
385/65R22.5	20PR	389	1072	164	5000	900	K	11.75	17



## BT219



- ▶ All position
- ▶ Applicable for regional and long haul on paved road

SIZE	PR	NEW TYRE INFLATED DIMENSIONS(mm)		LOAD INDEX	MAX.LOAD (kg)	PRESSURE	SPEED RATING	STANDARD RIM	TREAD DEPTH (mm)
		SECTION WIDTH	OVERALL DIAMETER						
11R22.5	14PR	279	1054	144/142	2800/2650	720/720	M	8.25	14.8
11R22.5	16PR	279	1054	146/143	3000/2725	830/830	M	8.25	14.8
12R22.5	14PR	300	1085	146/143	3000/2725	720/720	M	9.00	14.8
12R22.5	16PR	300	1085	150/147	3350/3075	830/830	L	9.00	14.8
12R22.5	18PR	300	1085	152/149	3550/3250	930/930	L	9.00	14.8
275/80R22.5	14PR	276	1012	145/143	2900/2725	750/750	L	8.25	15
275/80R22.5	16PR	276	1012	149/146	3250/3000	850/850	L	8.25	15
295/60R22.5	14PR	292	926	146/143	3000/2725	760/760	L	9.00	14.8
295/60R22.5	16PR	292	926	148/145	3150/2900	830/830	L	9.00	14.8
295/60R22.5	18PR	292	926	149/146	3250/3000	900/900	L	9.00	14.8
295/60R22.5	18PR	292	926	150/147	3350/3075	900/900	K	9.00	14.8
295/80R22.5	16PR	298	1044	150/147	3350/3075	830/830	L	9.00	14.8
295/80R22.5	18PR	298	1044	152/149	3550/3250	900/900	M	9.00	14.8
315/60R22.5	18PR	313	950	151/148	3450/3150	830/830	L	9.75	14.8
315/60R22.5	16PR	313	950	152/148	3550/3150	900/900	L	9.75	14.8
315/80R22.5	18PR	312	1076	154/151	3750/3450	830/830	M	9.00	15.5
315/80R22.5	20PR	312	1076	157/154	4125/3750	900/900	K	9.00	15.5
315/80R22.5	20PR	312	1076	156/150	4000/3350	850/850	L	9.00	15.5



## BT268



- ▶ For regional application of steer and trailer wheels
- ▶ Applicable for riding on normal and city road and high way
- ▶ With excellent water drainage and non-skid performance, fuel saving due to low rolling resistance
- ▶ The pattern is good in low heating up and high speed performance

SIZE	PR	NEW TYRE INFLATED DIMENSIONS(mm)		LOAD INDEX	MAX.LOAD (kg)	PRESSURE	SPEED RATING	STANDARD RIM	TREAD DEPTH (mm)
		SECTION WIDTH	OVERALL DIAMETER						
10.00R20	16PR	278	1054	146/143	3000/2725	830/830	L	7.5	16
10.00R20	18PR	278	1054	149/146	3250/3000	930/930	K	7.5	16
11.00R20	16PR	293	1085	150/147	3350/3075	830/830	L	8.0	17
11.00R20	18PR	293	1085	152/149	3550/3250	930/930	K	8.0	17



## BT288



- ▶ All position application
- ▶ Applicable to normal and good road
- ▶ With good anti-skid and irregular wear resistance
- ▶ Four grooves, low rolling resistance

SIZE	PR	NEW TYRE INFLATED DIMENSIONS(mm)		LOAD INDEX	MAX.LOAD (kg)	PRESSURE	SPEED RATING	STANDARD RIM	TREAD DEPTH (mm)
		SECTION WIDTH	OVERALL DIAMETER						
7.50R16LT	12PR	215	805	120/116	1400/1250	670/670	L	6.00G	11
7.50R16LT	14PR	215	805	122/118	1500/1320	770/770	L	6.00G	11
7.50R16LT	16PR	215	805	124/120	1600/1405	800/800	K	6.00G	11
7.50R16LT	16PR	215	805	124/120	1600/1405	800/800	L	6.00G	11
8.25R16LT	14PR	235	855	126/122	1700/1500	670/670	L	6.50H	12
8.25R16LT	16PR	235	855	128/124	1800/1600	770/770	K	6.50H	12
8.25R16LT	16PR	235	855	128/124	1800/1600	770/770	L	6.50H	12



## BT360



- ▶ For all position wheels
- ▶ Designed for light truck, agricultural vehicles and light dump truck.
- ▶ Excellent traction performance
- ▶ Low heating up shoulder design.

SIZE	PR	NEW TYRE INFLATED DIMENSIONS(mm)		LOAD INDEX	MAX.LOAD (kg)	PRESSURE	SPEED RATING	STANDARD RIM	TREAD DEPTH (mm)
		SECTION WIDTH	OVERALL DIAMETER						
6.50R16LT	10PR	185	750	107/102	975/850	560/560	M	5.50F	12
6.50R16LT	12PR	185	750	110/105	1060/925	670/670	L	5.50F	12
7.00R16LT	8PR	200	775	107/102	975/850	460/460	L	5.50F	14
7.00R16LT	12PR	200	775	115/110	1215/1060	670/670	M	5.50F	14
7.00R16LT	12PR	200	775	115/110	1215/1060	670/670	L	5.50F	14
7.00R16LT	14PR	200	775	118/114	1320/1180	770/770	L	5.50F	14
7.50R16LT	14PR	215	805	122/118	1500/1320	770/770	L	6.00G	16
7.50R16LT	16PR	215	805	124/120	1600/1405	800/800	K	6.00G	16
8.25R16LT	14PR	235	855	126/122	1700/1500	670/670	L	6.50H	16
8.25R16LT	16PR	235	855	128/124	1800/1600	770/770	K	6.50H	16
8.25R20	14PR	236	974	136/134	2240/2120	830/830	K	6.5	18
8.25R20	16PR	236	974	139/137	2430/2300	930/930	K	6.5	18
12R22.5	18PR	300	1085	152/149	3550/3250	930/930	L	9.00	17
12R22.5	18PR	320	1124	156/150	4000/3350	875/875	K	9.75	17
12R22.5	20PR	320	1124	156/153	4000/3650	930/930	K	9.75	17
315R22.5	18PR	312	1076	154/151	3750/3450	830/830	M	9.00	15.5
315R22.5	20PR	312	1076	156/150	4000/3350	850/850	L	9.00	15.5



## BT316



- ▶ Excellent anti-overloading and excellent wear resistance
- ▶ Wide tread and Complex groove angle to improve the irregular wear and long tread life

SIZE	PR	NEW TYRE INFLATED DIMENSIONS(mm)		LOAD INDEX	MAX.LOAD (kg)	PRESSURE	SPEED RATING	STANDARD RIM	TREAD DEPTH (mm)
		SECTION WIDTH	OVERALL DIAMETER						
325/95R24	22PR	325	1228	162/160	4750/4500	850/850	K	9.0	17



## BT369



- ▶ For long haul application of truck and all positions wheels on good roads;
- ▶ With wide tread design to extend tire service life;
- ▶ With excellent water drainage and heat dispersion performance;
- ▶ This pattern has performance in low heating up and rolling resistance.

SIZE	PR	NEW TYRE INFLATED DIMENSIONS(mm)		LOAD INDEX	MAX.LOAD (kg)	PRESSURE	SPEED RATING	STANDARD RIM	TREAD DEPTH (mm)
		SECTION WIDTH	OVERALL DIAMETER						
11.00R20	16PR	293	1085	150/147	3350/3075	830/830	L	8.0	17
11.00R20	18PR	293	1085	152/149	3550/3250	930/930	K	8.0	17
11R22.5	14PR	279	1054	144/142	2800/2650	720/720	L	8.25	17.5
11R22.5	16PR	279	1054	146/143	3000/2725	830/830	L	8.25	17.5
12R22.5	14PR	300	1085	146/143	3000/2725	720/720	L	9.00	18
12R22.5	16PR	300	1085	150/147	3350/3075	830/830	L	9.00	18
12R22.5	18PR	300	1085	152/149	3550/3250	930/930	L	9.00	18
12R22.5	18PR	300	1085	152/149	3550/3250	930/930	L	9.00	18
295/80R22.5	16PR	298	1044	150/147	3350/3075	830/830	L	9.00	18
295/80R22.5	18PR	298	1044	152/149	3550/3250	900/900	M	9.00	18
315/80R22.5	18PR	312	1076	154/151	3750/3450	830/830	M	9.00	18
315/80R22.5	20PR	312	1076	157/154	4125/3750	900/900	K	9.00	18
315/80R22.5	20PR	312	1076	156/150	4000/3350	850/850	L	9.00	18



## BT369N



- ▶ For long haul application of truck and all positions wheels on good roads;
- ▶ With wide tread design to extend tire service life;
- ▶ With excellent water drainage and heat dispersion performance;
- ▶ This pattern has performance in low heating up and rolling resistance.

SIZE	PR	NEW TYRE INFLATED DIMENSIONS(mm)		LOAD INDEX	MAX.LOAD (kg)	PRESSURE	SPEED RATING	STANDARD RIM	TREAD DEPTH (mm)
		SECTION WIDTH	OVERALL DIAMETER						
11R22.5	14PR	279	1054	144/142	2800/2650	720/720	L	8.25	17.5
11R22.5	16PR	279	1054	146/143	3000/2725	830/830	L	8.25	17.5
11R22.5	18PR	279	1050	148/145	3150/2900	850/850	L	8.25	17.5
12R22.5	14PR	300	1085	146/143	3000/2725	720/720	L	9.00	18
12R22.5	16PR	300	1085	150/147	3350/3075	830/830	L	9.00	18
12R22.5	18PR	300	1085	152/149	3550/3250	930/930	L	9.00	18
12R22.5	18PR	300	1085	152/149	3550/3250	930/930	L	9.00	18



## BT388/BT388N



- ▶ For regional application of drive axle
- ▶ Applicable to various road surface on freeway
- ▶ With good grip and traction performance
- ▶ Excellent wear resistance and long mileage

SIZE	PR	NEW TYRE INFLATED DIMENSIONS(mm)		LOAD INDEX	MAX.LOAD (kg)	PRESSURE	SPEED RATING	STANDARD RIM	TREAD DEPTH (mm)
		SECTION WIDTH	OVERALL DIAMETER						
11R22.5	14PR	279	1054	144/142	2800/2650	720/720	M	8.25	20
11R22.5	14PR	279	1054	144/142	2800/2650	720/720	L	8.25	20
11R22.5	16PR	279	1054	146/143	3000/2725	830/830	M	8.25	20
11R22.5	16PR	279	1054	146/143	3000/2725	830/830	L	8.25	20
11R22.5	16PR	279	1050	148/145	3150/2900	850/850	M	8.25	20
12R22.5	14PR	300	1085	146/143	3000/2725	720/720	L	9.00	20
12R22.5	14PR	300	1085	146/143	3000/2725	720/720	L	9.00	20
12R22.5	16PR	300	1085	150/147	3350/3075	830/830	L	9.00	20
12R22.5	16PR	300	1085	150/147	3350/3075	830/830	L	9.00	20
12R22.5	16PR	300	1084	152/148	3550/3150	850/850	M	9.00	20
12R22.5	18PR	300	1085	152/149	3550/3250	930/930	L	9.00	20
12R22.5	18PR	300	1085	152/149	3550/3250	930/930	L	9.00	20
12R22.5	18PR	300	1085	152/149	3550/3250	930/930	L	9.00	20
295/80R22.5	16PR	298	1044	150/147	3350/3075	830/830	L	9.00	20.5
295/80R22.5	16PR	298	1044	150/147	3350/3075	830/830	L	9.00	21
295/80R22.5	18PR	298	1044	152/149	3550/3250	900/900	M	9.00	20.5
295/80R22.5	18PR	298	1044	152/149	3550/3250	900/900	M	9.00	21
315/80R22.5	18PR	312	1076	154/151	3750/3450	830/830	M	9.00	21
315/80R22.5	18PR	312	1076	154/151	3750/3450	830/830	M	9.00	21
315/80R22.5	20PR	312	1076	157/154	4125/3750	900/900	K	9.00	21
315/80R22.5	20PR	312	1076	157/154	4125/3750	900/900	K	9.00	21
315/80R22.5	20PR	312	1076	156/150	4000/3350	850/850	L	9.00	21
315/80R22.5	20PR	312	1076	156/150	4000/3350	850/850	L	9.00	21
385/55R22.5	18PR	389	1072	158	4250	830	L	11.75	17
385/55R22.5	20PR	389	1072	160	4500	900	K	11.75	17



## BT389



- ▶ Aggressive, open-shoulder design helps deliver long tread life and traction.
- ▶ Extensive lug and siping to improve traction on wet and dry surfaces, and the extra-wide tread helps deliver added stability. Especially in deep snow

SIZE	PR	NEW TYRE INFLATED DIMENSIONS(mm)		LOAD INDEX	MAX LOAD (kg)	PRESSURE	SPEED RATING	STANDARD RIM	TREAD DEPTH (mm)
		SECTION WIDTH	OVERALL DIAMETER						
11R22.5	14PR	279	1054	144/142	2800/2650	720/720	M	8.25	21
11R22.5	16PR	279	1054	146/143	3000/2725	825/825	L	8.25	21
11R24.5	14PR	279	1104	146/143	3000/2725	720/720	M	8.25	21
11R24.5	16PR	279	1104	149/146	3250/3000	825/825	L	8.25	21



## BT398N



- ▶ Drive wheel application
- ▶ For standard load and high speed long haul application on paved road
- ▶ Deep grooves and wide tread design to extend tire service life
- ▶ Excellent brake and drive performance with special lug pattern design

SIZE	PR	NEW TYRE INFLATED DIMENSIONS(mm)		LOAD INDEX	MAX LOAD (kg)	PRESSURE	SPEED RATING	STANDARD RIM	TREAD DEPTH (mm)
		SECTION WIDTH	OVERALL DIAMETER						
10.00R20	16PR	278	1054	146/143	3000/2725	830/830	L	7.5	19.5
10.00R20	18PR	278	1054	149/146	3250/3000	930/930	K	7.5	19.5



## BT398+



- ▶ Mainly used for drive wheel
- ▶ For long haul application on paved road
- ▶ Deep tread depth and wide tread crown offers long mileage
- ▶ Unique tread block ensures good traction and brake performance

SIZE	PR	NEW TYRE INFLATED DIMENSIONS(mm)		LOAD INDEX	MAX LOAD (kg)	PRESSURE	SPEED RATING	STANDARD RIM	TREAD DEPTH (mm)
		SECTION WIDTH	OVERALL DIAMETER						
12R22.5	16PR	300	1085	146/143	3000/2725	720/720	L	9.00	24
12R22.5	16PR	300	1085	150/147	3350/3075	830/830	L	9.00	24
12R22.5	18PR	300	1085	152/149	3550/3250	930/930	L	9.00	24
315/80R22.5	18PR	312	1076	154/151	3750/3450	830/830	L	9.00	24
315/80R22.5	20PR	312	1076	157/154	4125/3750	900/900	K	9.00	24
315/80R22.5	20PR	312	1076	156/150	4000/3350	850/850	L	9.00	24



## BT518



- ▶ All position application
- ▶ Mainly for good road surface
- ▶ With good grip and excellent traction performance

SIZE	PR	NEW TYRE INFLATED DIMENSIONS(mm)		LOAD INDEX	MAX LOAD (kg)	PRESSURE	SPEED RATING	STANDARD RIM	TREAD DEPTH (mm)
		SECTION WIDTH	OVERALL DIAMETER						
385/65R22.5	18PR	389	1072	158	4250	830	L	11.75	17
385/65R22.5	20PR	389	1072	160	4500	900	K	11.75	17
385/65R22.5	20PR	389	1072	164	5000	900	K	11.75	17



## BT518N

- ▶ All position application
- ▶ Mainly for good road surface
- ▶ With good grip and excellent traction performance

SIZE	PR	NEW TYRE INFLATED DIMENSIONS(mm)		LOAD INDEX	MAX LOAD (kg)		PRESSURE	SPEED RATING	STANDARD RIM	TREAD DEPTH (mm)
		SECTION WIDTH	OVERALL DIAMETER		SINGLE/DUAL	SINGLE/DUAL (kg)				
11.00R20	16PR	293	1085	150/147	3350/3075	830/830	K	8.0	18	
11.00R20	18PR	293	1085	152/149	3550/3250	930/930	J	8.0	18	
12R22.5	16PR	300	1085	150/147	3350/3075	830/830	K	9.00	18	
12R22.5	18PR	300	1085	152/149	3550/3250	930/930	J	9.00	18	



## BT566



- ▶ Drive application for long haul and regional haul service
- ▶ Deep tread depth helps to provide long original life
- ▶ Aggressive tread pattern design helps to provide excellent traction
- ▶ Continuous shoulder ribs to fight irregular wear

SIZE	PR	NEW TYRE INFLATED DIMENSIONS(mm)		LOAD INDEX	MAX LOAD (kg)		PRESSURE	SPEED RATING	STANDARD RIM	TREAD DEPTH (mm)
		SECTION WIDTH	OVERALL DIAMETER		SINGLE/DUAL	SINGLE/DUAL (kg)				
11R22.5	16PR	279	1054	146/143	3000/2725	830/830	L	8.25	20.5	



## BT556



- ▶ Close shoulder design
- ▶ Mainly for drive wheel
- ▶ Fuel saving for low rolling resistance
- ▶ Excellent water drainage
- ▶ Excellent grip and traction performance

SIZE	PR	NEW TYRE INFLATED DIMENSIONS(mm)		LOAD INDEX	MAX LOAD (kg)		PRESSURE	SPEED RATING	STANDARD RIM	TREAD DEPTH (mm)
		SECTION WIDTH	OVERALL DIAMETER		SINGLE/DUAL	SINGLE/DUAL (kg)				
11R22.5	14PR	279	1054	144/142	2800/2650	720/720	L	8.25	20.5	
11R22.5	16PR	279	1054	146/143	3000/2725	830/830	L	8.25	20.5	
11R24.5	14PR	279	1104	146/143	3000/2725	720/720	L	8.25	20.5	
11R24.5	16PR	279	1104	149/146	3250/3000	830/830	L	8.25	20.5	
255/70R22.5	14PR	255	930	136/133	2240/2060	700/700	M	7.50	20.5	
255/70R22.5	16PR	255	930	140/137	2500/2300	800/800	M	7.50	20.5	
285/75R24.5	14PR	283	1050	144/141	2800/2575	760/760	L	8.25	20.5	
285/75R24.5	16PR	283	1050	147/144	3075/2800	830/830	L	8.25	20.5	
295/75R22.5	14PR	298	1014	144/141	2800/2575	760/760	L	9.00	20.5	
295/75R22.5	16PR	298	1014	146/143	3000/2725	830/830	L	9.00	20.5	




## BT568

- ▶ All position application
- ▶ Applicable for mix and bad road condition
- ▶ With good performance in anti-cracking and tear resistance
- ▶ The pattern has excellent performance in irregular wear resistance

SIZE	PR	NEW TYRE INFLATED DIMENSIONS(mm)		LOAD INDEX	MAX LOAD (kg)		PRESSURE	SPEED RATING	STANDARD RIM	TREAD DEPTH (mm)
		SECTION WIDTH	OVERALL DIAMETER		SINGLE/DUAL	SINGLE/DUAL (kg)				
10.00R20	16PR	278	1054	146/143	3000/2725	830/830	L	7.5	16.5	
10.00R20	16PR	278	1054	146/142	3000/2630	840/770	L	7.5	16.5	
10.00R20	18PR	278	1054	149/146	3250/3000	930/930	K	7.5	16.5	
11.00R20	16PR	293	1085	150/147	3350/3075	830/830	L	8.0	16.5	
11.00R20	18PR	293	1085	152/149	3550/3250	930/930	K	8.0	16.5	
12.00R24	18PR	315	1226	158/155	4250/3875	830/830	J	8.5	15	
12.00R24	20PR	315	1226	160/157	4500/4125	900/900	K	8.5	15	



## BT577



- ▶ Aggressive, open-shoulder design helps deliver
- ▶ Long tread life and traction
- ▶ Mainly for drive wheel
- ▶ Extensive block siping improves traction by slicing through water for a solid grip on wet roads.
- ▶ Light On/Off-Highway Service / Regional Haul Service
- ▶ Pickup & Delivery Service Long Haul Service / Regional Haul Service

SIZE	PR	NEW TYRE INFLATED DIMENSIONS(mm)		LOAD INDEX	MAX.LOAD (kg)	PRESSURE	SPEED RATING	STANDARD RIM	TREAD DEPTH (mm)
		SECTION WIDTH	OVERALL DIAMETER						
11R22.5	14PR	279	1054	144/142	2800/2650	720/720	M	8.25	20
11R22.5	16PR	279	1054	146/143	3000/2725	830/830	M	8.25	20
11R22.5	16PR	279	1050	148/145	3150/2900	850/850	M	8.25	20
11R24.5	14PR	279	1104	146/143	3000/2725	720/720	M	8.25	20
11R24.5	16PR	279	1104	149/146	3250/3000	830/830	L	8.25	20
285/75R24.5	14PR	283	1050	144/141	2800/2575	760/760	M	8.25	24
285/75R24.5	16PR	283	1050	147/144	3075/2800	830/830	L	8.25	24
295/75R22.5	14PR	298	1014	144/141	2800/2575	760/760	M	9.00	24



## BT618



- ▶ Applicable for drive axle
- ▶ Riding on normal and paved road conditions
- ▶ With good grip and traction performance
- ▶ Good wear resistance and long mileage, excellent high speed performance

SIZE	PR	NEW TYRE INFLATED DIMENSIONS(mm)		LOAD INDEX	MAX.LOAD (kg)	PRESSURE	SPEED RATING	STANDARD RIM	TREAD DEPTH (mm)
		SECTION WIDTH	OVERALL DIAMETER						
12R22.5	14PR	300	1085	146/143	3000/2725	720/720	M	9.00	18.3
12R22.5	16PR	300	1085	150/147	3350/3075	830/830	L	9.00	18.3
12R22.5	16PR	300	1084	152/148	3550/3150	850/850	M	9.00	18.3
12R22.5	18PR	300	1085	152/149	3550/3250	930/930	L	9.00	18.3
12R22.5	18PR	300	1085	152/149	3550/3250	930/930	L	9.00	18.3



## BT588



- ▶ Close shoulder design
- ▶ Mainly for drive wheel
- ▶ Fuel saving for low rolling resistance
- ▶ Excellent water drainage
- ▶ Excellent grip and traction performance

SIZE	PR	NEW TYRE INFLATED DIMENSIONS(mm)		LOAD INDEX	MAX.LOAD (kg)	PRESSURE	SPEED RATING	STANDARD RIM	TREAD DEPTH (mm)
		SECTION WIDTH	OVERALL DIAMETER						
11R22.5	14PR	279	1054	144/142	2800/2650	720/720	M	8.25	20
11R22.5	16PR	279	1054	146/143	3000/2725	830/830	M	8.25	20
11R22.5	16PR	279	1050	148/145	3150/2900	850/850	M	8.25	20
11R24.5	14PR	279	1104	146/143	3000/2725	720/720	M	8.25	20
11R24.5	16PR	279	1104	149/146	3250/3000	830/830	L	8.25	20
285/75R24.5	14PR	283	1050	144/141	2800/2575	760/760	M	8.25	24
285/75R24.5	16PR	283	1050	147/144	3075/2800	830/830	L	8.25	24
295/75R22.5	14PR	298	1014	144/141	2800/2575	760/760	M	9.00	24
295/80R22.5	16PR	298	1044	150/147	3350/3075	830/830	L	9.00	21
295/80R22.5	18PR	298	1044	152/149	3550/3250	900/900	M	9.00	21
315/80R22.5	18PR	312	1076	154/151	3750/3450	830/830	M	9.00	21
315/80R22.5	20PR	312	1076	157/154	4125/3750	900/900	K	9.00	21
315/80R22.5	20PR	312	1076	156/150	4000/3350	850/850	L	9.00	21



## BT666



- ▶ TT/TL Dual mode
- ▶ Excellent anti-overloading and excellent wear resistance
- ▶ Wide tread and Complex groove angle to improve the irregular wear and long tread life

SIZE	PR	NEW TYRE INFLATED DIMENSIONS(mm)		LOAD INDEX	MAX.LOAD (kg)	PRESSURE	SPEED RATING	STANDARD RIM	TREAD DEPTH (mm)
		SECTION WIDTH	OVERALL DIAMETER						
325/95R24	22PR	325	1228	162/160	4750/4500	850/850	K	9.0	17.5



## BT668



- ▶ Good loading capacity, low rolling resistance and low noise
- ▶ With excellent water drainage and skip performance
- ▶ Mainly for trailer wheel, also applicable for steer wheel
- ▶ Applicable for medium and high speed transportation on good roads

SIZE	PR	NEW TYRE INFLATED DIMENSIONS(mm)		LOAD INDEX	MAX LOAD (kg)	PRESSURE		SPEED RATING	STANDARD RIM	TREAD DEPTH (mm)
		SECTION WIDTH	OVERALL DIAMETER			SINGLE/DUAL	SINGLE/DUAL (kpa)			
385/55R22.5	18PR	389	1072	158	4250	830	L	11.75	15	
385/55R22.5	20PR	389	1072	160	4500	900	K	11.75	15	



## BT688



- ▶ Mainly for steer axle, especially applicable for high way and urban roads
- ▶ Applicable for normal and good road surface
- ▶ With good stable ability and wear resistance
- ▶ Comfortable and fuel saving

SIZE	PR	NEW TYRE INFLATED DIMENSIONS(mm)		LOAD INDEX	MAX LOAD (kg)	PRESSURE		SPEED RATING	STANDARD RIM	TREAD DEPTH (mm)
		SECTION WIDTH	OVERALL DIAMETER			SINGLE/DUAL	SINGLE/DUAL (kpa)			
275/70R22.5	14PR	276	958	142/139	2650/2430	760/760	M	8.25	14.8	
275/70R22.5	16PR	276	958	144/141	2800/2575	830/830	L	8.25	14.8	
275/70R22.5	16PR	276	958	144/141	2800/2575	830/830	M	8.25	14.8	
275/70R22.5	18PR	276	958	146/143	3000/2725	900/900	L	8.25	14.8	
275/70R22.5	16PR	276	958	148/145	3150/2900	900/900	M	8.25	14.8	
315/70R22.5	16PR	312	1014	149/146	3250/3000	760/760	L	9.00	15	
315/70R22.5	18PR	312	1014	151/148	3450/3150	830/830	L	9.00	15	
315/70R22.5	16PR	312	1014	152/148	3550/3150	850/850	M	9.00	15	
315/70R22.5	18PR	312	1014	154/150	3750/3350	900/900	M	9.00	15	



## BT669



- ▶ Mainly for trailer wheel
- ▶ Fuel saving for low rolling resistance
- ▶ Long mileage and low cost per mile

SIZE	PR	NEW TYRE INFLATED DIMENSIONS(mm)		LOAD INDEX	MAX LOAD (kg)	PRESSURE		SPEED RATING	STANDARD RIM	TREAD DEPTH (mm)
		SECTION WIDTH	OVERALL DIAMETER			SINGLE/DUAL	SINGLE/DUAL (kpa)			
11R22.5	14FR	279	1054	144/142	2800/2650	720/720	M	8.25	10	
11R22.5	16FR	279	1054	146/143	3000/2725	830/830	M	8.25	10	
11R24.5	14FR	279	1104	146/143	3000/2725	720/720	M	8.25	10	
11R24.5	16FR	279	1104	149/146	3250/3000	830/830	L	8.25	10	
255/70R22.5	14PR	255	930	136/133	2240/2060	700/700	M	7.50	10	
255/70R22.5	16PR	255	930	140/137	2500/2300	800/800	M	7.50	10	
255/70R22.5	16PR	255	930	140/137	2500/2300	830/830	M	7.50	10	
285/75R24.5	14PR	283	1050	144/141	2800/2575	760/760	M	8.25	10	
285/75R24.5	16PR	283	1050	147/144	3075/2800	830/830	L	8.25	10	
295/75R22.5	14PR	298	1014	144/141	2800/2575	760/760	M	9.00	10	
295/75R22.5	16PR	298	1014	146/143	3000/2725	830/830	L	9.00	10	



## BT718



- ▶ Mainly for short distance transportation
- ▶ On-off highway application
- ▶ High tread depth to provide long original tread life
- ▶ Open shoulder helps to provide good traction performance and self-cleaning capacity

SIZE	PR	NEW TYRE INFLATED DIMENSIONS(mm)		LOAD INDEX	MAX LOAD (kg)	PRESSURE		SPEED RATING	STANDARD RIM	TREAD DEPTH (mm)
		SECTION WIDTH	OVERALL DIAMETER			SINGLE/DUAL	SINGLE/DUAL (kpa)			
7.50R16LT	12PR	215	805	120/116	1400/1250	670/670	L	6.00G	13.5	
7.50R16LT	14PR	215	805	122/118	1500/1320	770/770	L	6.00G	13.5	
7.50R16LT	16PR	215	805	124/120	1600/1405	800/800	L	6.00G	13.5	
8.25R16LT	14PR	235	855	126/122	1700/1500	670/670	L	6.50H	15	
8.25R16LT	16PR	235	855	128/124	1800/1600	770/770	K	6.50H	15	
9.00R20	14PR	259	1019	141/139	2575/2430	790/790	K	7.0	17	
9.00R20	16PR	259	1019	144/142	2800/2650	900/900	K	7.0	17	
10.00R20	16PR	278	1054	146/143	3000/2725	830/830	K	7.5	18	
10.00R20	18PR	278	1054	149/146	3250/3000	930/930	K	7.5	18	



## BT926



- ▶ All position application
- ▶ Applicable to normal and good road
- ▶ With good anti-skid and irregular wear resistance
- ▶ Four grooves, low rolling resistance

SIZE	PR	NEW TYRE INFLATED DIMENSIONS(mm)		LOAD INDEX	MAX.LOAD (kg)		PRESSURE	SPEED RATING	STANDARD RIM	TREAD DEPTH (mm)
		SECTION WIDTH	OVERALL DIAMETER		SINGLE/DUAL	SINGLE/DUAL (kg)				
215/75R17.5	14PR	211	767	125/122	1650/1500	760/760	M	6.00	13	
215/75R17.5	16PR	211	767	127/124	1750/1600	830/830	J	6.00	13	
215/75R17.5	14PR	212	767	126/124	1700/1600	700/700	M	6.00	13	
215/75R17.5	16PR	212	767	135/133	2180/2060	850/850	J	6.00	13	
215/75R17.5	18PR	212	767	135/133	2180/2060	860/860	J	6.00	13	
225/70R19.5	12PR	226	811	125/123	1650/1550	660/660	M	6.75	13.5	
225/70R19.5	14PR	226	811	128/126	1800/1700	760/760	M	6.75	13.5	
235/75R17.5	12PR	233	797	124/121	1600/1450	660/660	M	6.75	13.5	
235/75R17.5	12PR	233	797	126/123	1700/1550	660/660	M	6.75	13.5	
235/75R17.5	14PR	233	797	129/126	1850/1700	760/760	M	6.75	13.5	
235/75R17.5	16PR	233	797	132/129	2000/1850	830/830	J	6.75	13.5	
235/75R17.5	16PR	233	797	143/141	2725/2575	860/860	J	6.75	13.5	
235/75R17.5	16PR	233	797	132/130	2000/1900	775/775	M	6.75	13.5	
235/75R17.5	18PR	233	797	143/141	2725/2575	875/875	J	6.75	13.5	
245/70R19.5	12PR	248	839	129/127	1850/1750	660/660	M	7.50	13.5	
245/70R19.5	14PR	248	839	133/131	2060/1950	760/760	M	7.50	13.5	
245/70R19.5	16PR	248	839	135/133	2180/2060	830/830	L	7.50	13.5	
245/70R19.5	16PR	248	839	136/134	2240/2120	825/825	M	7.50	13.5	
245/70R19.5	18PR	248	839	141/140	2575/2500	850/850	J	7.50	13.5	
9.5R17.5	18PR	240	842	143/141	2725/2575	875/875	M	6.75	12.5	



## BT957



- ▶ Mainly for drive wheels
- ▶ Applicable for medium and high speed riding on normal and good roads
- ▶ With excellent grip and traction performance

SIZE	PR	NEW TYRE INFLATED DIMENSIONS(mm)		LOAD INDEX	MAX.LOAD (kg)		PRESSURE	SPEED RATING	STANDARD RIM	TREAD DEPTH (mm)
		SECTION WIDTH	OVERALL DIAMETER		SINGLE/DUAL	SINGLE/DUAL (kg)				
215/75R17.5	14PR	211	767	125/122	1650/1500	760/760	M	6.00	14.5	
215/75R17.5	16PR	211	767	127/124	1750/1600	830/830	J	6.00	14.5	
215/75R17.5	14PR	212	767	126/124	1700/1600	700/700	M	6.00	14.5	
215/75R17.5	16PR	212	767	135/133	2180/2060	850/850	J	6.00	14.5	
225/70R19.5	12PR	226	811	125/123	1650/1550	660/660	M	6.75	15	
225/70R19.5	14PR	226	811	128/126	1800/1700	760/760	L	6.75	15	
235/75R17.5	12PR	233	797	124/121	1600/1450	660/660	M	6.75	15.4	
235/75R17.5	12PR	233	797	126/123	1700/1550	660/660	M	6.75	15.4	
235/75R17.5	14PR	233	797	129/126	1850/1700	760/760	M	6.75	15.4	
235/75R17.5	16PR	233	797	132/129	2000/1850	830/830	J	6.75	15.4	
235/75R17.5	16PR	233	797	132/130	2000/1900	775/775	M	6.75	15.4	
235/75R17.5	18PR	233	797	143/141	2725/2575	875/875	J	6.75	15.4	
245/70R19.5	12PR	248	839	129/127	1850/1750	660/660	M	7.50	16	
245/70R19.5	14PR	248	839	133/131	2060/1950	760/760	M	7.50	16	
245/70R19.5	16PR	248	839	135/133	2180/2060	830/830	L	7.50	16	
245/70R19.5	16PR	248	839	136/134	2240/2120	825/825	M	7.50	16	
245/70R19.5	18PR	248	839	141/140	2575/2500	850/850	J	7.50	16	
265/70R19.5	14PR	262	867	140/138	2500/2360	850/850	L	7.50	15.5	
265/70R19.5	14PR	262	867	137/134	2300/2120	760/760	L	7.50	15.5	
265/70R19.5	16PR	262	867	139/136	2430/2240	830/830	J	7.50	15.5	
265/70R19.5	18PR	262	867	143/141	2725/2575	850/850	J	7.50	15.5	
9.5R17.5	18PR	240	842	143/141	2725/2575	875/875	K	6.75	15.5	



## BT929



- ▶ All position
- ▶ Excellent high speed performance and good grip both on dry and wet road
- ▶ Good wear resistance and fuel saving
- ▶ Continuous pattern in the shoulder avoids tire irregular wear

SIZE	PR	NEW TYRE INFLATED DIMENSIONS(mm)		LOAD INDEX	MAX.LOAD (kg)		PRESSURE	SPEED RATING	STANDARD RIM	TREAD DEPTH (mm)
		SECTION WIDTH	OVERALL DIAMETER		SINGLE/DUAL	SINGLE/DUAL (kg)				
10R22.5	14PR	254	1019	141/139	2575/2430	790/790	M	7.50	14.5	
10R22.5	16PR	254	1019	144/142	2800/2650	900/900	L	7.50	14.5	
265/70R19.5	14PR	262	867	140/138	2500/2360	850/850	L	7.50	13.5	
265/70R19.5	14PR	262	867	137/134	2300/2120	760/760	L	7.50	13.5	
265/70R19.5	16PR	262	867	139/136	2430/2240	830/830	J	7.50	13.5	
265/70R19.5	18PR	262	867	143/141	2725/2575	850/850	J	7.50	13.5	



## BT968/968N



- ▶ Mainly for long haul application of steer wheel, also applicable for trailer wheel
- ▶ Applicable to ride on high way and good road with speed
- ▶ With good performance of water drainage and skid resistance
- ▶ Low heating up and low rolling resistance performance

SIZE	PR	NEW TYRE INFLATED DIMENSIONS(mm)		LOAD INDEX	MAX.LOAD (kg)		PRESSURE	SPEED RATING	STANDARD RIM	TREAD DEPTH (mm)
		SECTION WIDTH	OVERALL DIAMETER		SINGLE/DUAL	SINGLE/DUAL (kg)				
295/80R22.5	16PR	298	1044	150/147	3350/3075	830/830	M	9.00	15	
295/80R22.5	16PR	298	1044	150/147	3350/3075	830/830	M	9.00	15	
295/80R22.5	18PR	298	1044	152/149	3550/3250	900/900	M	9.00	15	
295/80R22.5	18PR	298	1044	152/149	3550/3250	900/900	M	9.00	15	
295/80R22.5	18PR	298	1044	152/149	3550/3250	900/900	M	9.00	15	
315/80R22.5	18PR	312	1076	154/151	3750/3450	830/830	M	9.00	15	
315/80R22.5	20PR	312	1076	157/154	4125/3750	900/900	K	9.00	15	
315/80R22.5	20PR	312	1076	156/150	4000/3350	850/850	L	9.00	15	