

Xiamen Business Corporation

Address: Room 2206, BaiTong Building No. 47

JingKou Road - Qingdao City- China

Email: Sales@xiamenbusiness.com

TRUCK & BUS TYRES

PRODUCT CATALOGUE

2023



SECURE D02

- Suitable for long-distance mixed road transportation
- The rubber in the middle of the crown is highly saturated, durable and wear-resistant, and the longitudinal groove design has good heat dissipation performance
- Excellent block pattern design to achieve maximum power transmission

POSITION



PARAMETER

SIZE	LOAD INDEX	SPEED INDEX	PR	TREAD DEPTH (MM)	RIM
11R22.5	146/143	M	16	20.0	8.25
11R22.5	148/145	M	18	20.0	8.25
12R22.5-N	152/149	M	18	20.0	9.00
315/80R22.5	156/150	M	20	20.0	9.00
295/80R22.5-BZ	152/149	M	18	20.0	9.00
275/80R22.5	149/146	M	16	19.0	8.25
315/70R22.5	156/150L(154/150M)		18	20.0	9.00
215/75R17.5	135/133	J	18	15.0	6.00
235/75R17.5	143/141	J	18	15.0	6.75
225/70R19.5	128/126	M	14	15.0	6.75
245/70R19.5	136/134	M	16	15.0	7.50
265/70R19.5	140/138	M	16	15.0	7.50
265/70R19.5	140/138	M	18	15.0	7.50
285/70R19.5	148/145	M	16	16.0	8.25
315/60R22.5	154/148M	L	20	※	8.25
285/70R19.5	146/144L(144/142M)		18	16.0	8.25



SECURE ST42

- Suitable for national roads, high-speed and high-grade paved roads
- Effectively prevents side slips and provides good carrying performance
- Good heat dissipation and stone ejector
- Excellent durability and wear resistance

POSITION



PARAMETER

SIZE	LOAD INDEX	SPEED INDEX	PR	TREAD DEPTH (MM)	RIM
11R22.5	146/143	M	16	15.0	8.25
12R22.5-BZ	152/149	M	18	16.5	9.00
315/80R22.5	158/150L(154/150M)		20	16.0	9.00
295/80R22.5-BZ	152/149	M	18	15.0	9.00
275/80R22.5	149/146	M	16	14.0	8.25
315/70R22.5	156/150L(154/150M)		18	15.0	9.00
315/60R22.5	154/148	M	18	15.0	9.00
12R22.5-N	152/149	M	18	16.5	9.00

1N: Adding one layer of nylon wrapper can effectively enhance the strength of the bead and improve the overloading performance.



SECURE T31

- Suitable for national road, high speed and high-grade paving road
- Provide excellent steering and anti-skid performance
- Good performance in self-cleaning in addition to stone removal, prevent tread cracks
- Reduce tread heat and have good abrasion resistance

POSITION



PARAMETER

SIZE	LOAD INDEX	SPEED INDEX	PR	TREAD DEPTH (MM)	RIM
385/65R22.5	160	K	20	15.0	11.75
385/55R22.5	160K/158L		20	15.0	12.25
425/65R22.5	165	K	20	15.0	12.25
445/65R22.5	169	K	20	15.0	13.00
435/50R19.5	160	J	18	15.0	※
445/45R19.5	160	J	22	15.0	※



SECURE A61

- Applicable to national highway, high speed and high various comprehensive pavements
- Especially suitable for medium and long distance transportation, with good steering performance

POSITION



PARAMETER

SIZE	LOAD INDEX	SPEED INDEX	PR	TREAD DEPTH (MM)	RIM	SIZE	LOAD INDEX	SPEED INDEX	PR	TREAD DEPTH (MM)	RIM
11R22.5	146/143	M	16	15.0	8.25	11R24.5	149/146	M	16	15.0	8.25
11R22.5	148/145	M	18	15.0	8.25	12R24.5	154/151	K	18	16.0	9.00
12R22.5-BZ	152/149	M	18	16.0	9.00	7.50R16LT	122/118	L	14	13.0	6.00G
12R22.5-N	152/149	M	18	16.0	9.00	7.50R16LT	122/118	L	14	13.0	5.5J
12.00R20	156/153	L	20	16.5	8.50	6.50R16LT	110/105	M	12	9.5	5.50F
11.00R20	152/149	L	18	17.0	8.0	7.00R16LT	118/114	M	14	10.5	5.50F
315/80R22.5	156/150	M	20	16.0	9.00	7.00R16LT	118/114	M	14	10.5	5.5J
13R22.5-W	156/150	L	18	17.0	9.75	12.00R24-BZ	160/157	K	20	17.5	8.50
13R22.5-1N	156/153	L	20	17.0	9.75	12.00R24-1N	160/157	K	20	17.5	8.50
9.00R20	144/142	L	16	15.5	7.0	12.00R24-2N	160/157	K	20	17.5	8.50
10.00R20	149/146	L	18	16.5	7.50	265/70R19.5	143/141	M	18	15.0	7.50
8.25R16LT	128/124	L	16	13.0	6.50H	325/95R24	162/160	K	22	17.5	9.00
8.25R16LT-1N	128/124	L	16	13.0	6.50H	325/95R24-1N	162/160	K	22	17.5	9.00
11R24.5	146/143	M	14	15.0	8.25						



SECURE D01

- Suitable for national high way and high-grade paved roads
- Improved pattern design effectively avoids uneven wear
- Better grip with excellent driving and braking performance; excellent wear resistance

POSITION



SECURE D03

- Suitable for medium- and short-distance transportation on mixed roads
- The pattern has certain directionality and excellent traction performance
- Thick carcass structure has a good durability, not easy to be broken and separated.

POSITION



PARAMETER

SIZE	LOAD INDEX	SPEED INDEX	PR	TREAD DEPTH (MM)	RIM
385/65R22.5	160	J	20	15.0	11.75
425/65R22.5	165	J	20	17.5	12.25
445/65R22.5	169	K	20	18.0	13.00

PARAMETER

SIZE	LOAD INDEX	SPEED INDEX	PR	TREAD DEPTH (MM)	RIM
315/80R22.5	156/150	M	20	20.0	9.00
13R22.5-W	156/150	L	18	17.5	9.75
13R22.5-1N	156/150	L	18	17.5	9.75



SECURE D09

- Applicable to national highway, high speed and high grade pavement
- It is suitable for long-distance load transportation;
- Typical block pattern design, tires have excellent ability to grasp the ground, so that the vehicle in the operation of good traction, braking performance, widened tread running surface design, so that the tire has a good use cycle.

POSITION



SECURE ST41

- Applicable to national highway, high speed and high grade pavement
- Especially suitable for medium and long distance transportation, with good guiding performance.
- Features: anti-sideslip, good drainage, heat dissipation performance, decorative pattern ditch anti-clamping stone design long mileage.

POSITION



PARAMETER

SIZE	LOAD INDEX (S/D)	SPEED INDEX	PR	TREAD DEPTH (MM)	RIM
385/80R22.5	156/150	L	20	22.0	9.00

PARAMETER

SIZE	LOAD INDEX	SPEED INDEX	PR	TREAD DEPTH (MM)	RIM	SIZE	LOAD INDEX	SPEED INDEX	PR	TREAD DEPTH (MM)	RIM
11R22.5	144/142	M	14	※	8.25	225/70R19.5	128/126	M	14	12.5	6.75
11R22.5	146/143	M	16	14.0	8.25	245/70R19.5	136/134	M	16	12.5	7.50
295/75R22.5	144/141	M	14	※	9.00	265/70R19.5	140/138	M	16	※	7.50
295/75R22.5	146/143	M	16	14.0	9.00	265/70R19.5	143/141	J	18	12.5	7.50
11R24.5	146/143	M	14	※	8.25	275/70R22.5	144/141	M	16	※	8.25
11R24.5	149/146	M	16	14.0	8.25	275/70R22.5	148/145	M	18	14.0	8.25
285/75R24.5	144/141	M	14	※	8.25	255/70R22.5	140/137	M	16	14.0	7.50
285/75R24.5	146/143	M	16	14.0	8.25	285/70R19.5	150/148	J	18	13.0	8.25
215/75R17.5	135/133	J	18	12.5	6.00	285/70R19.5	148/145	M	16	※	8.25
235/75R17.5	143/141	J	18	12.5	6.75						



SECURE ST43

- Suitable for national roads, high-speed and high-grade paved roads
- Effectively prevents side slips and provides good carrying performance
- Good heat dissipation and stone ejector;
- Excellent durability and wear resistance.

POSITION



SECURE ST44

- Suitable for national roads, high-speed and high-grade paved roads
- Effectively prevents side slips and provides good carrying performance
- Good heat dissipation and stone ejector
- Excellent durability and wear resistance.

POSITION



PARAMETER

SIZE	LOAD INDEX	SPEED INDEX	PR	TREAD DEPTH (MM)	RIM
295/60R22.5	150/147	M	18	14.5	9.00

PARAMETER

SIZE	LOAD INDEX	SPEED INDEX	PR	TREAD DEPTH (MM)	RIM
295/60R22.5	150/147	M	18	14.5	9.00



SECURE ST47

- Suitable for national highway, high speed and high-grade pavement.

POSITION



PARAMETER

SIZE	LOAD INDEX	SPEED INDEX	PR	TREAD DEPTH (MM)	RIM
12R22.5-BZ	152/149	K	18	16.5	9.00
315/80R22.5	156/150	M	20	15.0	9.00



SECURE ST49

- Applicable to national highway, high speed and high grade pavement;
- Especially suitable for medium and long distance transportation, with good guiding performance;
- Features: anti-sideslip, good drainage, heat dissipation performance, decorative pattern ditch anti-stone design, high mileage.

POSITION



PARAMETER


SIZE	LOAD INDEX	SPEED INDEX	PR	TREAD DEPTH (MM)	RIM
315/80R22.5	156/150	L	20	16.0	9.00



SECURE M91

- Large solid pattern block, with excellent anti-cutting performance
- The reinforced carcass has excellent load performance
- The service life of the deep pattern is longer
- Transverse through pattern groove has excellent climbing and passing performance

POSITION



○ RECOMMEND

PARAMETER

SIZE	LOAD INDEX	SPEED INDEX	PR	TREAD DEPTH (MM)	RIM
12.00R20	156/153	F	20	25.5	8.50



SECURE M92

- Large solid pattern block, with excellent anti-cutting performance
- The reinforced carcass has excellent load performance
- The service life of the deep pattern is longer
- Transverse through pattern groove has excellent climbing and passing performance.

POSITION



○ RECOMMEND

PARAMETER

SIZE	LOAD INDEX	SPEED INDEX	PR	TREAD DEPTH (MM)	RIM
12.00R20	156/153	F	20	25.5	8.50



SECURE D04

- Applicable to national highway, high speed and high grade pavement
- Especially suitable for medium and long-distance load transportation
- Features: the pattern design has good heat dissipation performance, anti-friction and anti-skid performance of the tire shoulder, not easy to groove and crack of the pattern, and high comprehensive mileage

POSITION



PARAMETER

SIZE	LOAD INDEX	SPEED INDEX	PR	TREAD DEPTH (MM)	RIM
11R22.5	144/142	M	14	※	8.25
11R22.5	146/143	M	16	11.0	8.25
295/75R22.5	144/141	M	14	※	9.00
295/75R22.5	146/143	M	16	11.0	9.00
11R24.5	146/143	M	14	※	8.25
11R24.5	149/146	M	16	11.0	8.25
285/75R24.5	144/141	M	14	※	8.25
285/75R24.5	146/143	M	16	11.0	8.25



SECURE T32

- Suitable for national highway, high speed and high-grade pavement
- With good guiding performance, it is especially suitable for medium - and long-distance transportation
- Features: Sideslip resistance, excellent performance of drainage and heat dissipation, anti-stone trapping design In pattern groove, high mileage

POSITION



PARAMETER

SIZE	LOAD INDEX	SPEED INDEX	PR	TREAD DEPTH (MM)	RIM
11R22.5	144/142	M	14	※	8.25
11R22.5	146/143	M	16	21.0	8.25
295/75R22.5	144/141	M	14	※	9.00
295/75R22.5	146/143	M	16	21.0	9.00
11R24.5	146/143	M	14	※	8.25
11R24.5	149/146	M	16	21.0	8.25
285/75R24.5	144/141	M	14	※	8.25
285/75R24.5	146/143	M	16	21.0	8.25



SECURE T33

- Suitable for national roads, high-speed and high-grade paved roads
- Provide excellent steering and non-slip performance
- Good self-cleaning performance in addition to stone discharge, prevents tread cracks
- Reducing the heat from the tread has good wear resistance

POSITION



PARAMETER

SIZE	LOAD INDEX	SPEED INDEX	PR	TREAD DEPTH (MM)	RIM
11R22.5	146/143	M	16	17.5	8.25
12R22.5-BZ	152/149	M	18	18.0	9.00
12R22.5	152/149	M	18	18.0	9.00
315/80R22.5	156/150	M	20	18.0	9.00
295/80R22.5-1N	152/149	M	18	17.5	9.00
295/80R22.5-1N	152/149	M	18	17.5	9.00
13R22.5-W	154/151	M	18	20.0	9.75
13R22.5-1N	154/151	M	18	20.0	9.75



SECURE T33H

- Suitable for national roads, high-speed and high-grade paved roads
- Provide excellent steering and non-slip performance
- Good self-cleaning performance in addition to stone discharge, prevents tread cracks
- Reducing the heat from the tread has good wear resistance

POSITION



PARAMETER

SIZE	LOAD INDEX	SPEED INDEX	PR	TREAD DEPTH (MM)	RIM
11R22.5	146/143	M	16	17.5	8.25



SECURE ST42+

- Suitable for national roads, high-speed and high-grade paved roads
- Effectively prevents side slips and provides good carrying performance
- Good heat dissipation and stone ejector
- Excellent durability and wear resistance

POSITION



SECURE ST42S

- Suitable for national roads, high-speed and high-grade paved roads
- Effectively prevents side slips and provides good carrying performance
- Good heat dissipation and stone ejector
- Excellent durability and wear resistance

POSITION



PARAMETER

SIZE	LOAD INDEX	SPEED INDEX	PR	TREAD DEPTH (MM)	RIM
12R22.5-BZ	152/149	M	18	16.00	9.00

PARAMETER

SIZE	LOAD INDEX	SPEED INDEX	PR	TREAD DEPTH (MM)	RIM
295/80R22.5-1N	152/149	M	18	15.0	9.00



SECURE ST42S+

- Suitable for national roads, high-speed and high-grade paved roads
- Effectively prevents side slips and provides good carrying performance
- Good heat dissipation and stone ejector
- Excellent durability and wear resistance

POSITION



SECURE D07

- For short-haul national roads and high-speed heavy duty operations
- Unique deep pattern design of tire crown, long life
- Strong ground grasping performance, can be excellent transmission-driving force.

POSITION



PARAMETER

SIZE	LOAD INDEX	SPEED INDEX	PR	TREAD DEPTH (MM)	RIM
295/80R22.5-2N	152/149	M	18	15.0	9.00

PARAMETER

SIZE	LOAD INDEX	SPEED INDEX	PR	TREAD DEPTH (MM)	RIM
12R22.5-N	152/149	M	18	19.0	9.00



SECURE D08

- Suitable for national highways, high-speed and high-grade paving roads
- Optimized pattern design effectively avoids uneven wear
- Good grip and excellent driving and braking performance
- Good abrasion resistance

POSITION



SECURE D11

- The design of three tread patterns in the middle of the tread provides good steering and anti-sideslip performance for the tire
- The wide tread design and high wear resistance formula ensure excellent wear resistance
- Optimize contour design to ensure uniform force on each block of tread and prevent irregular wear
- The use of high strength tire body and steel belt (CCST) greatly improves the service life of the tire

POSITION



PARAMETER

SIZE	LOAD INDEX	SPEED INDEX	PR	TREAD DEPTH (MM)	RIM
12R22.5-N	152/149	M	18	22.0	9.00

PARAMETER

SIZE	LOAD INDEX	SPEED INDEX	PR	TREAD DEPTH (MM)	RIM
11R22.5	146/143	L	16	21.5	8.25



SECURE T34

- Longitudinal three groove pattern design, the small steel plate in the pattern is connected to the small grooves, which is beneficial to heat dissipation, drainage and anti-slip
- Deepen the pattern design, high saturation, high wear resistance formula and high mileage.
- It is suitable for general pavement roads. The pattern edge block is treated to resist abnormal abrasion, and the sidewall rubber is thickened and scratch resistant.

POSITION



SECURE A68

- Suitable for national highway, high speed and high-grade pavement
- With good guiding performance, it is especially suitable for medium-andlong-distance transportation
- Features: Sideslip resistance, excellent performance of drainage andheat dissipation, anti-stone trapping design in pattern groove, highmileage.

POSITION



PARAMETER

SIZE	LOAD INDEX	SPEED INDEX	PR	TREAD DEPTH (MM)	RIM
11R22.5	148/145	J	18	21.0	8.25

PARAMETER

SIZE	LOAD INDEX	SPEED INDEX	PR	TREAD DEPTH (MM)	RIM
12R22.5-BZ	152/149	K	18	16.5	9.00



SECURE ST45

- The pattern design has anti-stone, good heat dissipation and drainage performance
- It is suitable for high-speed and high-grade paved roads and trailers
- The guide tug wheel of the matching performance8, effectively prevents side slip, and provides good carrying vehicle has good control performance
- It has excellent wear resistance, low heat generation, low rolling resistance, environmental protection and fuel saving.

POSITION



SECURE ST46

- The pattern design has anti-stone, good heat dissipation and drainage performance
- It is suitable for high-speed and high-grade paved roads and trailers
- The guide tug wheel of the matching vehicle has good control performance, effectively prevents side slip, and provides good carrying performance
- It has excellent wear resistance, low heat generation, low rolling resistance, environmental protection and fuel saving.

POSITION



PARAMETER

SIZE	LOAD INDEX	SPEED INDEX	PR	TREAD DEPTH (MM)	RIM
12R22.5-BZ	152/149	M	18	16.0	9.00

PARAMETER

SIZE	LOAD INDEX	SPEED INDEX	PR	TREAD DEPTH (MM)	RIM
12R22.5-BZ	152/149	M	18	16.0	9.00



SECURE D18

- Suitable for mixed road of short and medium distance
- Transverse deformation pattern design, especially suitable for heavyload transportation with poor pavement
- The reinforced body structure has excellent load performance
- Deepen the pattern and wide driving surface to make the tires have longer service life.

POSITION



SECURE T36

- The pattern design has anti-stone, good heat dissipation performance and drainage performance.
- It is suitable for high-speed and high-grade paved roads and trailers. The guide tug wheel of the matching vehicle has good control performance, effectively prevents side slip, and provides good carrying performance.
- It has excellent wear resistance, low heat generation, low rolling resistance, environmental protection and fuel saving.

POSITION



PARAMETER

SIZE	LOAD INDEX	SPEED INDEX	PR	TREAD DEPTH (MM)	RIM
12R22.5-N	152/149	K	18	22.5	9.00

PARAMETER

SIZE	LOAD INDEX	SPEED INDEX	PR	TREAD DEPTH (MM)	RIM
12R22.5-N	152/149	L	18	18.5	9.00



SECURE T37

POSITION



- The pattern design has stone ejector, good heat dissipation performance and drainage performance
It is suitable for high-speed and high-grade paved roads and trailers
- The steering/ trailer wheel of the matching vehicle has good control performance, effectively prevents side slip, and provides good carrying performance
- It has excellent wear resistance, low heat generation, low rolling resistance, environmental protection and fuel saving



SECURE D16

POSITION



- The block pattern design widens the driving surface and effectively realizes the uniform distribution of pressure. The shoulder stiffeners deal with the periodical use of growth and are inlaid with zigzag steel sheets, which is conducive to the mutual support of the patterns and the water passing between the grooves.
- It has good heat dissipation performance and drainage performance, and good driving and braking performance.

PARAMETER

SIZE	LOAD INDEX	SPEED INDEX	PR	TREAD DEPTH (MM)	RIM
12R22.5-N	152/149	K	18	18.5	9.00

PARAMETER

SIZE	LOAD INDEX	SPEED INDEX	PR	TREAD DEPTH (MM)	RIM
12R22.5-N	152/149	K	18	22.0	9.00



SECURE T35

- The new pattern design of three grooves, the bottom of the groove is equipped with anti-stone elastic rubber, strengthens the bottom of the groove to resist puncture and prevents cracks, and has good heat dissipation and drainage performance.
- The handling performance is good, effectively preventing the abnormal grinding and breaking of the tail flicking block, and providing good carrying performance.

POSITION



SECURE M95

- Large block pattern, with excellent anti-cutting performance
- The reinforced body structure has excellent load performance
- Typical transverse pattern groove has excellent climbing and passing performance.

POSITION



PARAMETER

SIZE	LOAD INDEX	SPEED INDEX	PR	TREAD DEPTH (MM)	RIM
12R22.5-N	152/149	K	18	19.0	9.00

PARAMETER


SIZE	LOAD INDEX	SPEED INDEX	PR	TREAD DEPTH (MM)	RIM
12.00R20	156/153	E	20	25.5	8.50



SECURE M98

- Large solid pattern block, with excellent anti-cutting performance
- The reinforced carcass has excellent load performance
- The service life of the deep pattern is more long
- Transverse through pattern groove has excellent climbing and passing performance.

POSITION



RECOMMEND

PARAMETER

SIZE	LOAD INDEX	SPEED INDEX	PR	TREAD DEPTH (MM)	RIM
11.00R20	152/149	E	18	24.5	8.0



SECURE D14

- Suitable for national highway and good paved road.
- It is suitable for long-distance load transportation.
- Classical mahjong block pattern design makes sure that tires have excellent ability to grasp the ground. When the vehicle during working, it has good traction/braking performance.
- 10% bigger tread width enlarges the footprint and improves the mileage.

POSITION



RECOMMEND

PARAMETER

SIZE	LOAD INDEX	SPEED INDEX	PR	TREAD DEPTH (MM)	RIM
315/80R22.5	156/150	M	20	21.0	9.00

- This size is wide treadth



SECURE D02S

- Suitable for long-distance mixed road transportation.
- The rubber in the middle of the crown is highly saturated, durable and wear-resistant, and the longitudinal groove design has good heat dissipation performance.
- Excellent block pattern design to achieve maximum power transmission.

POSITION



SECURE D02S+

- Suitable for long-distance mixed road transportation.
- The rubber in the middle of the crown is highly saturated, durable and wear-resistant, and the longitudinal groove design has good heat dissipation performance.
- Excellent block pattern design to achieve maximum power transmission.

POSITION



PARAMETER

SIZE	LOAD INDEX	SPEED INDEX	PR	TREAD DEPTH (MM)	RIM
295/80R22.5-1N	152/149	M	18	20.0	9.00

PARAMETER

SIZE	LOAD INDEX	SPEED INDEX	PR	TREAD DEPTH (MM)	RIM
295/80R22.5-2N	152/149	M	18	20.0	9.00



SECURE D17

- The pattern design has anti-stone, good heat dissipation performance and drainage performance.
- Suitable for high-speed and high-grade paved road van trucks and towed vehicles transportation operations.
- It has excellent wear resistance, low heat generation, low rolling resistance, environmental protection and fuel saving.

POSITION



SECURE A67

- Suitable for mixed road of short and medium distance.
- Transverse deformation pattern design, especially suitable for heavy load transportation with poor pavement.
- The reinforced body structure has excellent load performance.
- Deepen the pattern and wide driving surface to make the tires have a longer service life.

POSITION



PARAMETER

SIZE	LOAD INDEX	SPEED INDEX	PR	TREAD DEPTH (MM)	RIM
245/70R19.5	144/142	J	18	16.0	7.50

PARAMETER

SIZE	LOAD INDEX	SPEED INDEX	PR	TREAD DEPTH (MM)	RIM
245/70R19.5	144/142	J	18	14.8	7.50



SECURE D13

- Mixed directional pattern design, horizontal steel sheet connection, good drainage performance, good heat dissipation performance, superior grip and driving performance, anti-skid, low rolling resistance, is a novel pattern design.
- With deep pattern and high wear resistance and low heat generation formula design, the tire has a longer service life.

POSITION



SECURE D12

- Mixed block directional pattern design, horizontal grooves connected, strong driving and braking force, large pattern blocks, strong integrity, and superior gripping and driving performance.
- With deep pattern and high wear resistance and low heat generation formula design, the tire has a long service life.
- The pattern has strong integrity, not easy to collapse and block, low heat.

POSITION



PARAMETER

SIZE	LOAD INDEX	SPEED INDEX	PR	TREAD DEPTH (MM)	RIM
12R22.5-BZ	152/149	J	18	19.0	9.00

PARAMETER

SIZE	LOAD INDEX	SPEED INDEX	PR	TREAD DEPTH (MM)	RIM
12R22.5-BZ	152/149	J	18	19.0	9.00



SECURE M99

- Block pattern design, horizontal grooves are connected, the middle large block supports, and has excellent grasping and passing performance.
- It is suitable for the leading level of construction and construction sites for a variety of short- and medium-distance vehicles; generation formula design, puncture resistance.

POSITION



PARAMETER

SIZE	LOAD INDEX	SPEED INDEX	PR	TREAD DEPTH (MM)	RIM
12R22.5-BZ	152/149	J	18	22.0	9.00



SECURE D21

- Mixed pattern design, with 3D steel inlaid in the flower block, the pattern is novel.
- Especially suitable for medium and long-distance operations on icy, snowy and muddy roads, with strong grip and excellent safety performance.
- The pattern has good drainage and heat dissipation performance, suitable for high-grade roads and high speeds.
- Deepen the pattern and high wear resistance formula design to extend the service life of the tire.

POSITION



PARAMETER

SIZE	LOAD INDEX	SPEED INDEX	PR	TREAD DEPTH (MM)	RIM
11R22.5	146/143	L	16	22.0	8.25



SECURE ST48

- Hybrid drive pattern ultra-wide tread design, strong pattern grip, good driving and braking safety performance, and good pattern drainage performance.
- Patterned ultra-wide driving surface design, more uniform pressure distribution, crown design with large arcs, excellent grounding marks, shoulder reinforcement design, increase durability.
- Low rolling resistance, low heat generation, low noise, energy saving and environmental protection.

POSITION



SECURE D15

- Hybrid drive pattern ultra-wide tread design, strong pattern grip, good driving and braking safety performance, and good pattern drainage performance.
- Patterned ultra-wide driving surface design, more uniform pressure distribution, crown design with large arcs, excellent grounding marks, shoulder reinforcement design, increase durability.
- Low rolling resistance, low heat generation, low noise, energy saving and environmental protection.

POSITION



PARAMETER

SIZE	LOAD INDEX	SPEED INDEX	PR	TREAD DEPTH (MM)	RIM
295/80R22.5	152/149	L	18	16.5	9.00

PARAMETER

SIZE	LOAD INDEX	SPEED INDEX	PR	TREAD DEPTH (MM)	RIM
295/80R22.5	152/149	L	18	22.0	9.00



SECURE D19

- Mixed directional pattern design, strong grip ability, strong driving type, suitable for the assembly of various vehicle driving wheel positions.
- The side block pattern has strong integrity, and the middle block groove has good heat dissipation performance, and it is not easy to cause crown voids and crown explosions.
- Deeper pattern and high wear resistance formula design prolongs the service life of tires and has high mileage.

POSITION



SECURE M93

- Specially designed for harsh road conditions.

POSITION



PARAMETER

SIZE	LOAD INDEX	SPEED INDEX	PR	TREAD DEPTH (MM)	RIM
11R22.5	146/143	L	16	21.5	8.25

PARAMETER

SIZE	LOAD INDEX	SPEED INDEX	PR	TREAD DEPTH (MM)	RIM
235/75R17.5	143/141	J	18	17.00	6.75
325/95R24	162/160	K	22	23.50	9.00
325/95R24-1N	162/160	K	22	23.50	9.00
315/80R22.5-1N	158/156	J	22	22.00	9.00



SECURE D05

- Suitable for short/middle distance on mix road.
- Special pattern design provides good traction and transmission performance, and excellent wear resistance.
- Reinforced carcass make sure longer mileage.

POSITION



SECURE M94

- Specially designed for harsh road conditions.
- Features: Excellent load capacity tear resistant, wear resistance, transmission and handling performance.
- Reinforced carcass and bead provide better performance under heavy load condition.

POSITION



PARAMETER

SIZE	LOAD INDEX	SPEED INDEX	PR	TREAD DEPTH (MM)	RIM
11R22.5	146/143	K	16	18.5	8.25
12R22.5-N	152/149	J	18	22.0	9.00

PARAMETER

SIZE	LOAD INDEX	SPEED INDEX	PR	TREAD DEPTH (MM)	RIM
12R22.5-N	152/149	J	18	24.0	9.00
295/80R22.5-2N	152/149	J	18	22.5	9.00
11R22.5	148/145	J	18	24.5	8.25
325/95R24	162/160	K	22	※	9.00
325/95R24-1N	162/160	K	22	※	9.00



SECURE D23

- Unique block design, with good driving performance and braking performance.
- High wear resistance formula, tear resistance, wear resistance, high mileage.
- High strength tire carcass and bellt, strong tire carcass, good pressure resistance.

POSITION



SECURE A61W

- Applicable to national highway, high speed and high various comprehensive pavements.
- Especially suitable for medium and long distance transportation, with good steering performance.
- Features: anti-sideslip, good drainage performance and heat dissipation performance, Anti-stone trapping groove design, high mileage.

POSITION



PARAMETER

SIZE	LOAD INDEX	SPEED INDEX	PR	TREAD DEPTH (MM)	RIM
12.00R20	156/153	K	20	19.0	8.50
13R22.5-2N	154/151	F	18	21.0	9.75

PARAMETER

SIZE	LOAD INDEX	SPEED INDEX	PR	TREAD DEPTH (MM)	RIM
12.00R20	156/153	L	20	16.5	8.50
11.00R20	152/149	L	18	17.0	8.0
315/80R22.5	156/150	M	20	15.0	9.00



SECURE D06

- Large horizontal tread pattern provides high-strength tread formula.
- Improved tread adhesive enhances anti-cutting performance.
- Strong structure improves overload performance.

POSITION



PARAMETER

SIZE	LOAD INDEX	SPEED INDEX	PR	TREAD DEPTH (MM)	RIM
12.00R20	156/153	L	20	18.5	8.50
11.00R20	152/149	L	18	18.0	8.0
10.00R20	149/146	L	18	18.0	7.50
8.25R16LT	128/124	L	16	16.0	6.50H
7.50R16LT	122/118	L	14	15.5	6.00G
12.00R24-BZ	160/157	K	20	20.0	8.50
12.00R24-1N	160/157	K	20	20.0	8.50
325/95R24	162/160	K	22	20.0	9.00
325/95R24-1N	162/160	K	22	20.0	9.00



SECURE A62

- Applicable to national highway, high speed and high grade pavement.
- Especially suitable for medium and long distance transportation, with good guiding performance.
- Features: anti-eccentric wear, anti-sideslip, good drainage, heat dissipation, decorative pattern ditch anti-stone design, good comprehensive performance, high mileage.

POSITION



PARAMETER


SIZE	LOAD INDEX	SPEED INDEX	PR	TREAD DEPTH (MM)	RIM
12.00R20	156/153	L	20	18.0	8.50
11.00R20	152/149	L	18	16.5	8.0



SECURE M96

- Large solid pattern block, with excellent anti-cutting performance.
- The reinforced carcass has excellent load performance.
- Deepen the pattern and wide driving surface to make the tires have a longer service life.

POSITION



RECOMMEND

PARAMETER

SIZE	LOAD INDEX	SPEED INDEX	PR	TREAD DEPTH (MM)	RIM
12.00R20	156/153	E	20	24.0	8.50
11.00R20	152/149	E	18	23.0	8.0



SECURE M97

- Large solid pattern block, with excellent anti-cutting performance.
- The reinforced carcass has excellent load performance.
- The service life of the deep pattern is more long.
- Transverse through pattern groove has excellent climbing and passing performance.

POSITION



PARAMETER


SIZE	LOAD INDEX	SPEED INDEX	PR	TREAD DEPTH (MM)	RIM
12.00R20	156/153	E	20	25.5	8.50
11.00R20	152/149	E	18	24.5	8.0
12R22.5-N	152/149	E	18	24.5	9.00



SECURE A63

- The tire adopts special tread formula, the crown part adopts high-wear-resisting rubber; the inner layer adopts low-hot-rolled rubber.
- Unique tire shoulder design enhances the anti-wear performance and prevent abnormal wear.
- Good drainage performance, Good driving stability, low fuel consumption low noise.

POSITION



○ RECOMMEND

PARAMETER

SIZE	LOAD INDEX	SPEED INDEX	PR	TREAD DEPTH (MM)	RIM
12.00R24-BZ	160/157	K	20	14.5	8.50
12.00R24-1N	160/157	K	20	14.5	8.50
325/95R24	162/160	K	22	15.5	9.00
325/95R24-1N	162/160	K	22	15.5	9.00
325/95R24-2N	162/160	K	22	15.5	9.00

- 2N: Adding double-layer nylon wrapper greatly enhances the strength of the bead and improves the anti-load performance.



SECURE A64

- Suitable for short-distance mixed road.
- It is especially suitable for short-distance work with high load, and the optimized tread design effectively avoids uneven wear.
- The low heat composite matrix ensures high mileage and the small zigzag tread design improves grip.

POSITION



PARAMETER

SIZE	LOAD INDEX	SPEED INDEX	PR	TREAD DEPTH (MM)	RIM
12.00R24-BZ	160/157	K	20	14.5	8.50
12.00R24-1N	160/157	K	20	14.5	8.50
325/95R24	162/160	K	22	15.5	9.00
325/95R24-1N	162/160	K	22	15.5	9.00



SECURE A65

- Suitable for mixed road of short and medium distance.
- Transverse deformation pattern design, especially suitable for heavy load transportation with poor pavement.
- The reinforced body structure has excellent load performance.
- Deepen the pattern and wide driving surface to make the tires have a longer service life.

POSITION



PARAMETER

SIZE	LOAD INDEX	SPEED INDEX	PR	TREAD DEPTH (MM)	RIM
11R22.5	148/145	J	18	21.5	8.25
275/70R22.5	148/145	K	18	21.5	8.25



SECURE A66

- Excellent pattern design, with excellent traction and braking.
- Tire tread pattern groove heat dissipation efficiency, excellent drainage performance.
- Special formula structure design, small rolling resistance, wear resistance, oil saving.

POSITION



PARAMETER

SIZE	LOAD INDEX	SPEED INDEX	PR	TREAD DEPTH (MM)	RIM
12.00R20	156/153	K	20	16.0	8.5
11.00R20	152/149	K	18	16.3	8.0
11.00R20	152/149	K	18	16.3	8.0
13R22.5-W	156/153	L/K	20	18.0	9.75
10.00R20	149/146	L	18		7.50
325/95R24	162/160	K	22		9.00
325/95R24-1N	162/160	K	22	15.5	9.00



SECURE D24

- Excellent pattern design, block with better drive and grip.
- Optimized and strengthened bead design, with excellent bearing-capacity.
- High wear resistance, low heat generation, deep groove pattern, improve the service life of tires.

POSITION



SECURE S22

- Suitable for national roads, high-speed and high-grade paved roads.
- Effectively prevents side slips and provides good carrying performance.
- Good heat dissipation and stone ejector.
- Excellent durability and wear resistance.

POSITION



PARAMETER

SIZE	LOAD INDEX	SPEED INDEX	PR	TREAD DEPTH (MM)	RIM
12.00R20	156/153	K	20	18.0	8.5
11.00R20	152/149	K	18	18.5	8.0

PARAMETER

SIZE	LOAD INDEX	SPEED INDEX	PR	TREAD DEPTH (MM)	RIM
11R22.5	148/145	M	18	14.5	8.25
315/80R22.5	156/150	M	20	15.0	9.00
295/80R22.5	152/149	M	18	15.0	9.00



SECURE S21

- Applicable to national highway, high speed and high various comprehensive pavements.
- Especially suitable for medium and long distance transportation, with good steering performance.
- Features: anti-sideslip, good drainage performance and heat dissipation performance, stone ejector design, high mileage.

POSITION



SECURE D42

- Typical mixed pattern design of mahjong blocks, with good tear resistance, puncture resistance and high wear resistance.
- The tires have excellent grip on the ground, and the vehicles have good traction and braking performance during operation.
- The pattern is a variable pitch directional type, which increases the transmission of driving force of the pattern, reduces the noise during driving, has high saturation of the driving surface, good drainage and heat dissipation performance.
- It is suitable for medium and long distance transportation of various models and high-grade road conditions.

POSITION



PARAMETER

SIZE	LOAD INDEX	SPEED INDEX	PR	TREAD DEPTH (MM)	RIM
11R22.5	148/145	M	18	14.5	8.25
315/80R22.5	156/150	M	20	15.0	9.00

PARAMETER

SIZE	LOAD INDEX	SPEED INDEX	PR	TREAD DEPTH (MM)	RIM
295/80R22.5	152/149	L	18PR	20.0	9.00
315/80R22.5	156/150	L	20PR	20.0	9.00



SECURE D43

- Suitable for short/medium-distance on mixed road.
- The pattern has certain directionality and excellent traction performance.
- Thick carcass structure has a good durability, not easy to be broken and separated.

POSITION



SECURE D41

- Applicable to national highway, high speed and high grade pavement.
- Especially suitable for medium and long-distance load transportation.
- Features: the pattern design has good heat dissipation performance, anti-friction and anti-skid performance of the tire shoulder, not easy to groove and crack of the pattern, and high comprehensive mileage.

POSITION



PARAMETER

SIZE	LOAD INDEX	SPEED INDEX	PR	TREAD DEPTH (MM)	RIM
295/80R22.5	152/149	K	18	20.0	9.00
315/80R22.5	156/150	K	20	20.0	9.00

PARAMETER

SIZE	LOAD INDEX	SPEED INDEX	PR	TREAD DEPTH (MM)	RIM
11R22.5	148/145	M	18	20.0	8.25



SECURE T11

- Four-zigzag pattern design with variable pitch enjoy good drainage guidance and anti-slip performance. The pattern groove adopts 3D high-strength steel sheet technology.
- The pattern block is smooth and clean, preventing the dust, with excellent and long-lasting cooling effect.
- High wear-resistant formula is suitable for long-distance operation and high mileage in a variety of vehicles.

POSITION



PARAMETER

SIZE	LOAD INDEX	SPEED INDEX	PR	TREAD DEPTH (MM)	RIM
385/65R22.5	160	L	20	15.0	11.75



SECURE T12

- The pattern design of four longitudinal grooves adopts the variable pitch design.
- The pattern design and processing technology of the knurled rubber effectively solve the chronic problem of the longitudinal pattern with stones.
- It has good drainage and passing performance, energy saving, low rolling resistance, low noise, green and environmental protection. The formula design is suitable for medium and long distance operation of various vehicles, with high mileage and multiple renovations.

POSITION



PARAMETER

SIZE	LOAD INDEX	SPEED INDEX	PR	TREAD DEPTH (MM)	RIM
385/65R22.5	160	L	20	15.0	11.75