



APLUS
High Performance Tyres

APLUS
High Performance Tyres

| LONG HAUL | REGIONAL | ON&OFF ROAD | MINING |

XIÀMÉN
BUSINESS CORPORATION

www.xiamenbusiness.com

**PASS
UNIMPEDED**

LONG HAUL

01-10

REGIONAL

11-18

ON&OFF MIXED

19-28

MINING

29-32



S201



D801



S602



D280



S600



D805



T306



D800



S201+



D801+



S618



D288



D268



D807



T605



D860



S202



D808



S901



D318



D608



D820



T609



D880



S205



D909



S902



T705



D688



D876



D818



S207



T706



S903



T708



D802



D878



S208



T707



D188



D803



D900



LONG HAUL

PRODUCT MANUALS

PAGE:01-10



S201

Position: ALL Position



- High density, flexomatic blading, for outstanding braking on wet surfaces combined with high mileage.
- Groove bottom protectors help deliver additional defense against stone drilling.
- More mileage and greater lateral stability.

Size	RIM	P.R.	Pattern	L./S.R.	Max load(kg)		S.W. mm	O.D. mm	T.D. mm
	inch				Single	Dual			
9.5R17.5	6.75	18	S201	143/141J	2725	2575	232	836	12.5
215/75R17.5	6.00	16	S201	127/124M	1750	1600	211	767	12
215/75R17.5	6.00	18	S201	135/133J	2180	2060	211	767	12
235/75R17.5	6.75	16	S201	132/130M	2000	1850	233	797	12.5
235/75R17.5	6.75	18	S201	143/141J	2725	2575	233	797	12.5
225/70R19.5	6.75	14	S201	128/126M	1800	1700	226	811	12.5
245/70R19.5	7.50	16	S201	136/134M	2240	2120	248	839	12.5
245/70R19.5	7.50	18	S201	143/141J	2725	2575	248	839	12.5
265/70R19.5	7.50	16	S201	140/138M	2500	2360	260	862	12.5
265/70R19.5	7.50	18	S201	143/141J	2725	2575	260	862	12.5
285/70R19.5	8.25	16	S201	146/144M	3000	2800	282	886	13
285/70R19.5	8.25	18	S201	150/148J	3350	3150	282	886	13
255/70R22.5	7.50	16	S201	140/137M	2500	2300	251	926	14
275/70R22.5	8.25	16	S201	148/145M	3150	2900	216	952	14.5
275/70R22.5	8.25	18	S201	152/148J	3550	3150	216	952	14.5
275/80R22.5	8.25	18	S201	149/146M	3250	3000	288	1011	14.5
315/70R22.5	9.00	20	S201	154/150M	3750	3350	312	1014	15
385/55R22.5	12.25	20	S201	160L	4500	4500	383	996	15.5
295/75R22.5	9.00	16	S201	146/143M	3000	2725	298	1011	15.5
295/75R22.5	9.00	18	S201	148/145L	3150	2900	288	1011	14.5
295/80R22.5	9.00	18	S201	154/151M	3750	3450	292	1036	15.5
315/80R22.5	9.00	20	S201	157/154M	4125	3750	312	1076	15.5
385/65R22.5	11.75	20	S201	160L	4500	4500	389	1071	15.5
11R22.5	8.25	18	S201	149/146M	3250	3000	268	1043	14.5
12R22.5	9.00	18	S201	152/149M	3550	3250	300	1075	14.5
11R24.5	8.25	18	S201	152/149L	3550	3250	279	1095	14.5
285/75R24.5	8.25	16	S201	147/144M	3075	2800	283	1050	15.5
8.25R20	6	16	S201	139/137	2430	2300	234	970	15



S201+ PREMIUM

Position: ALL Position



- Widened and deepened pattern help enhance the load capacity.
- Wide tread increase the contact area with the ground and improve the heat-sinking capacity.
- Symmetric pattern design ensure the uniform wear of tire and keep more mileage and it's better for retreading.

Size	RIM	P.R.	Pattern	L./S.R.	Max load(kg)		S.W.	O.D.	T.D.
	inch				Single	Dual			
295/80R22.5	9.00	18	S201+	154/151M	3750	3450	292	1036	15.5



S202 PREMIUM

Position: ALL Position



- New designed pattern, suitable for well paved road condition with high speed level and excellent durability.
- Tread rubber compound for fine drainage and grip performance which improved outstandingly.
- Heavy loading capacity, low heat build-up, high speed and low noise.

Size	RIM	P.R.	Pattern	L./S.R.	Max load(kg)		S.W.	O.D.	T.D.
	inch				Single	Dual			
11R22.5	9.00	18	S202	152/149L	3550	3250	296	1080	17
12R22.5	9.00	18	S202	152/149L	3550	3250	300	1080	17
295/60R22.5	9.00	18	S202	150/147M	3350	3075	292	916.5	14.5
295/80R22.5	9.00	18	S202	152/149M	3550	3250	292	1034	14.5
315/60R22.5	9.75	20	S202	156/150L	4000	3350	312	950	14.5
315/70R22.5	9.00	18	S202	154/150M	3750	3350	312	1014	15
315/80R22.5	9.00	20	S202	157/154M	4125	3750	310	1074	15.5



S205

Position: ALL Position



- Premium five-rib tread with various micro sipes to provide high mileage, even wear, low noise.
- Wide, flat tread optimizes footprint shape for improved handling and response in long haul service.
- Latest technology carcass geometry and materials for enhanced damage resistance, durability.

Size	RIM	P.R.	Pattern	L./S.R.	Max load(kg)		S.W.	O.D.	T.D.
	inch				Single	Dual			
11R22.5	8.25	18	S205	149/146M	3250	3000	268	1040	13
12R22.5	9.00	18	S205	152/149M	3550	3250	300	1075	14.5
255/70R22.5	7.50	16	S205	140/137M	2500	2300	251	926	11
295/75R22.5	9.00	16	S205	146/143M	3000	2725	298	1011	11
295/75R22.5	9.00	18	S205	148/145L	3150	2900	298	1004	11
295/80R22.5	9.00	18	S205	152/149M	3550	3250	292	1034	14.5
315/80R22.5	9.00	20	S205	156/150M	4000	3350	312	1076	14.5
11R24.5	8.25	16	S205	149/146M	3250	3000	279	1104	11
11R24.5	8.25	18	S205	152/149M	3550	3250	279	1088	11
285/75R24.5	8.25	16	S205	147/144M	3075	2800	283	1050	11



S207 PREMIUM

Position: ALL Position



- Optimized contour and balanced footprint distribution for extended tread life and product performance.
- Outstanding Self-cleaning tread design and grooves reduce stone retention and ensure good performance on the highway.
- Special tread compound for outstanding mileage and heat reduction.

Size	RIM	P.R.	Pattern	L.I/S.R.	Max load(kg)		S.W.	O.D.	T.D.
	inch				Single	Dual			
11R22.5	8.25	18	S207	149/146M	3250	3000	279	1043	15.5
12R22.5	9.00	18	S207	152/149L	3550	3250	296	1082	18
295/80R22.5	9.00	18	S207	154/151M	3750	3450	292	1036	15.5



S208

Position: ALL Position



- Outstanding self-cleaning tread design promote adaptability in long haul road conditions.
- High density, flexomatic blading, for outstanding braking on wet surfaces combined with high mileage.
- More mileage and greater lateral stability.

Size	RIM	P.R.	Pattern	L.I/S.R.	Max load(kg)		S.W.	O.D.	T.D.
	inch				Single	Dual			
9.5R17.5	6.75	18	S208	143/141J	2725	2575	232	836	12.5
12R22.5	9.00	18	S208	152/149M	3550	3250	296	1075	14.5
315/80R22.5	9.00	20	S208	156/150M	4000	3350	312	1076	15.5



D801

Position: Drive Position



- Bridged center block design helps improve tread stability.
- Special tread compound and tire casing offers good tire mileage for price sensitive customers.
- Wide tread design guarantees good traction for highway service in allseason conditions.

Size	RIM	P.R.	Pattern	L.I/S.R.	Max load(kg)		S.W.	O.D.	T.D.
	inch				Single	Dual			
9.5R17.5	6.75	18	D801	143/141J	2725	2575	232	843	16
215/75R17.5	6.00	16	D801	127/124M	1750	1600	211	767	15
215/75R17.5	6.00	18	D801	135/133J	2180	2060	211	767	15
235/75R17.5	6.75	16	D801	132/130M	2000	1850	233	797	15.5
235/75R17.5	6.75	18	D801	143/141J	2725	2575	233	797	15.5
225/70R19.5	6.75	14	D801	128/126M	1800	1700	226	811	15.5
245/70R19.5	7.50	16	D801	136/134M	2240	2120	248	839	15.5
245/70R19.5	7.50	18	D801	143/141J	2725	2575	248	839	15.5
265/70R19.5	7.50	16	D801	140/138M	2500	2360	260	868	15.5
265/70R19.5	7.50	18	D801	143/141J	2725	2575	260	868	15.5
285/70R19.5	8.25	16	D801	146/144M	3000	2800	282	892	16
285/70R19.5	8.25	18	D801	150/148J	3350	3150	282	892	16
10.00R20	7.50	18	D801	149/146K	3250	3000	278	1058	20
11R22.5	8.25	18	D801	149/146M	3250	3000	268	1054	20
275/70R22.5	8.25	16	D801	148/145M	3150	2900	216	959	18
275/70R22.5	8.25	18	D801	152/148J	3550	3150	216	959	18
315/70R22.5	9.00	20	D801	154/150M	3750	3350	312	1014	20
295/75R22.5	9.00	16	D801	146/143K	3000	2725	298	1014	20
295/80R22.5	9.00	18	D801	154/151M	3750	3450	292	1045	20
315/80R22.5	9.00	20	D801	156/150M	4000	3350	312	1076	20
11R24.5	8.25	16	D801	149/146K	3250	3000	279	1104	20
275/80R22.5	8.25	18	D801	149/146M	3250	3000	288	1022	20



D801+

PREMIUM

Position: Drive Position



- Bridged center block design helps improve tread stability.
- Special tread compound and tire casing offers good tire mileage for price sensitive customers.
- Wide tread design guarantees good traction for highway service in all season conditions.

Size	RIM	P.R.	Pattern	L./S.R.	Max load(kg)		S.W.	O.D.	T.D.
	inch				Single	Dual			
295/80R22.5	9.00	18	D801+	154/151M	3750	3450	292	1045	20



D909

PREMIUM

Position: Drive Position



- The mixed pattern design and the latest 3D steel sipe technology provide excellent traction and braking and extend tire life.
- Stone ejectors in all tread grooves help to reduce stone drilling and protect belts to extend tire life.
- Increased footprint contact area delivers superior traction and resists irregular wear.

Size	RIM	P.R.	Pattern	L./S.R.	Max load(kg)		S.W.	O.D.	T.D.
	inch				Single	Dual			
11R22.5	8.25	18	D909	149/146M	3250	3000	279	1057	21.5



D808

Position: Drive Position



- Extra deep tread with stone drilling protectors to promote long original mileage.
- Optimised bead area construction for better durability.
- Closed -shoulder tread design provides even wear while maintaining excellent traction.

Size	RIM	P.R.	Pattern	L./S.R.	Max load(kg)		S.W.	O.D.	T.D.
	inch				Single	Dual			
11R22.5	8.25	18	D808	149/146M	3250	3000	268	1054	20
295/75R22.5	9.00	16	D808	146/143K	3000	2725	298	1022	20
295/75R22.5	9.00	18	D808	148/145L	3150	2900	288	1022	20
11R24.5	8.25	18	D808	152/149L	3550	3250	279	1106	20
285/75R24.5	8.25	16	D808	147/144L	3075	2800	283	1050	20
275/80R22.5	8.25	18	D808	149/146M	3250	3000	288	1022	20





T706

Position: Trailer Position



- Dual compound rubber helps ensure cool operating temperatures while abrasion resistant upper tread helps keep wear rates low.
- Lateral sipes along rib edges help enhance traction and braking in adverse weather conditions.
- Optimized bead area construction for better durability.



T707

PREMIUM

Position: ALL Position



- Wide tread and new profile design make the grounding more uniform and better wear resistance.
- Individually designed tread compound makes the pattern more wear-resistant under pavement.
- The use of high-strength carcass and belt steel wire provides excellent tire load-carrying performance.

Size	RIM	P.R.	Pattern	L.I/S.R.	Max load(kg)		S.W.	O.D.	T.D.
	inch				Single	Dual			
215/75R17.5	6.00	16	T706	127/124M	1750	1600	210	766	12
215/75R17.5	6.00	18	T706	135/133J	2180	2060	210	766	12
235/75R17.5	6.75	16	T706	132/130M	2000	1850	233	797	12.5
235/75R17.5	6.75	18	T706	143/141J	2725	2575	210	766	12
225/70R19.5	6.75	14	T706	128/126M	1800	1700	224	809	12.5
245/70R19.5	7.50	16	T706	136/134M	2240	2120	248	839	12.5
245/70R19.5	7.50	18	T706	143/141J	2725	2575	210	766	12
265/70R19.5	7.50	16	T706	140/138M	2500	2360	260	862	12.5
265/70R19.5	7.50	18	T706	143/141J	2725	2575	260	862	12.5
275/70R22.5	8.25	16	T706	148/145M	3150	2900	276	958	14.5
285/70R19.5	8.25	16	T706	146/144M	3000	2800	282	886	13
285/70R19.5	8.25	18	T706	150/148J	3350	3150	282	886	13
385/55R22.5	12.25	20	T706	160L	4500	4500	383	996	15.5
385/65R22.5	11.75	20	T706	160L	4500	4500	389	1071	15.5
425/65R22.5	12.25	22	T706	166K	5300	—	355	1144	15.5
445/65R22.5	13.00	20	T706	169K	5800	—	454	1144	15.5

Size	RIM	P.R.	Pattern	L.I/S.R.	Max load(kg)		S.W.	O.D.	T.D.
	inch				Single	Dual			
385/65R22.5	11.75	24	T707	164K	5000	5000	380	1074	15.5
445/45R19.5	15.00	24	T707	164K	5000	5000	394	894	15





REGIONAL

PRODUCT MANUALS



S602

Position:ALL Position



- Four folded tread grooves designed to provide excellent dry and wet grip performance.
- Wider shoulder design to reduce tire wear.
- Low thermal tread compound to improve the usage life of tires

Size	RIM	P.R.	Pattern	L./S.R.	Max load(kg)		S.W. mm	O.D. mm	T.D. mm
	inch				Single	Dual			
7.00R16	5.50F	14	S602	118/114L	1320	1180	202	768	11



S618

Position:ALL Position



- Premium five-rib tread with SILICA compound features longer tire life with low rolling resistance
- Latest technology carcass geometry and materials for enhanced damage resistance, durability and loading capacity.
- Computer aided carcass design helps improve footprint for better mileage performance.

Size	RIM	P.R.	Pattern	L./S.R.	Max load(kg)		S.W. mm	O.D. mm	T.D. mm
	inch				Single	Dual			
7.50R16	6.00G	14	S618	122/118L	1500	1320	215	800	13
8.25R16	6.50H	16	S618	128/124K	1800	1600	225	848	11.5
11.00R20	8.00	18	S618	152/149K	3550	3250	288	1079	16



S901

Position: ALL Position



- Special designed tread with SILICA compound features longer tire life with low rolling resistance.
- Low heat build-up, even load distribution for longer mileage and reduced tire wear.
- Optimized bead area construction for better durability.

Size	RIM	P.R.	Pattern	L./S.R.	Max load(kg)		S.W.	O.D.	T.D.
	inch				Single	Dual			
12.00R24	8.50	20	S901	160/157K	4500	4125	315	1226	16



S903

Position: ALL Position



- More mileage and greater lateral stability.
- Low heat tread design, even load distribution for longer mileage and reduced tire wear.
- Optimized bead area construction for better durability.

Size	RIM	P.R.	Pattern	L./S.R.	Max load(kg)		S.W.	O.D.	T.D.
	inch				Single	Dual			
12.00R24	8.50	18	S903	158/155K	4250	3875	315	1226	16
12.00R24	8.50	20	S903	160/157K	4500	4125	315	1226	16



S902

Position: ALL Position



- Longer wear life & service life.
- Improved irregular wear resistance.
- Improved cut/chipping resistance.

Size	RIM	P.R.	Pattern	L./S.R.	Max load(kg)		S.W.	O.D.	T.D.
	inch				Single	Dual			
12.00R24	8.50	20	S902	160/157K	4500	4125	315	1226	16



D188

PREMIUM

Position: Drive Position



- Wider tread and special tread compound provide excellent traction and improved wear resistance, extending tire mileage.
- The belt widening technology increases the tire crown buffer area, increases stiffness and improves penetration resistance.
- Extra load-carrying capacity with a specially reinforced tire bead and optimized contour.

Size	RIM	P.R.	Pattern	L./S.R.	Max load(kg)		S.W.	O.D.	T.D.
	inch				Single	Dual			
295/80R22.5	9.00	18	D188	154/151M	3750	3450	292	1049	22



D280

Position: Drive Position



- Wide, flat tread optimizes footprint shape for improved handling and response in long haul service.
- Vertical and horizontal pattern design promotes soft soil mobility and drive property.
- Better structure ensure driving safety and longer mileage

Size	RIM	P.R.	Pattern	L.I./S.R.	Max load(kg)		S.W.	O.D.	T.D.
	inch				Single	Dual			
12R22.5	9.00	18	D280	152/149K	3550	3250	296	1090	22



D318

PREMIUM

Position: Drive Position



- Anti-wear performance provide the longer mileage, widen tread design increases the contact area and improves the anti-wear ability.
- Open shoulder designs, the block pattern offer excellent drive force and anti-peeling performance on paved and unpaved roads.
- Widened tread design ensures safty control during driving, optimize the bead design and improves the durability greatly, reducing the bead faul trate.

Size	RIM	P.R.	Pattern	L.I./S.R.	Max load(kg)		S.W.	O.D.	T.D.
	inch				Single	Dual			
295/60R22.5	9.00	18	D318	150/147M	3350	3075	292	923.5	18
315/60R22.5	9.75	20	D318	156/150L	4000	3350	313	950	18.5
315/70R22.5	9.00	18	D318	154/150M	3750	3350	312	1014	23
315/80R22.5	9.00	20	D318	157/154M	4125	3750	310	1083	20



D288

PREMIUM

Position: Drive Position



- With double tread design, the upper layer improves wear resistance, the lower layer reduces heat generation and increases the service life of the tire.
- Shoulder block design and special tread formula can reduce uneven wear and improve wear performance.
- The design of longitudinal and lateral mixed pattern improves the driving, braking and anti-wet slip performance of the tire.

Size	RIM	P.R.	Pattern	L.I./S.R.	Max load(kg)		S.W.	O.D.	T.D.
	inch				Single	Dual			
315/80R22.5	9.00	20	D288	157/154M	4125	3750	310	1087	22



T705

Position: Trailer Position



- Five deep circumferential grooves for excellent water evacuation and wet traction.
- Low heat sidewall design, even load distribution for longer mileage and reduced tire wear.
- Optimized bead area construction for better durability.

Size	RIM inch	P.R.	Pattern	L.I/S.R.	Max load(kg)		S.W. mm	O.D. mm	T.D. mm
					Single	Dual			
385/65R22.5	11.75	20	T705	160L	4500	4500	389	1071	15.5



T708

PREMIUM

Position: Trailer Position



- Wide tread and new profile design make the grounding more uniform and better wear resistance.
- Individually designed tread compound makes the pattern more adaptable on mixed roads.
- The use of high-strength carcass and belt steel wire provides excellent tire load-carrying performance.

Size	RIM inch	P.R.	Pattern	L.I/S.R.	Max load(kg)		S.W. mm	O.D. mm	T.D. mm
					Single	Dual			
385/65R22.5	11.75	24	T708	164K	5000	5000	380	1071	17





S600

Position: ALL Position



- ▶ Latest technology carcass geometry and materials for enhanced damage resistance, durability and loading capacity.
- ▶ Premium Zigzag design promotes soft soil mobility.
- ▶ Offset block shoulder design with SILICA compound promotes good traction and abrasion resistance

Size	RIM	P.R.	Pattern	L.I./S.R.	Max load(kg)		S.W. mm	O.D. mm	T.D. mm
	inch				Single	Dual			
7.00R16LT	5.50F	14	S600	118/114L	1320	1180	202	768	11
7.50R16	6.00G	14	S600	122/118L	1500	1320	215	800	13
8.25R16	6.50H	16	S600	128/124K	1800	1600	225	848	11.5
8.25R20	6.50	16	S600	139/137K	2430	2300	234	970	15
9.00R20	7.00	16	S600	144/142K	2800	2650	260	1018	15.5
10.00R20	7.50	18	S600	149/146K	3250	3000	278	1051	16.5
11.00R20	8.00	18	S600	152/149K	3550	3250	288	1079	16
12.00R20	8.50	20	S600	156/153K	4000	3650	309	1115	16.3
11R22.5	8.25	18	S600	149/146M	3250	3000	268	1043	14.5
12R22.5	9.00	18	S600	152/149M	3550	3250	300	1075	14.5
13R22.5	9.75	20	S600	156/150L	4000	3350	320	1124	15.5
11R24.5	8.25	18	S600	152/149M	3550	3250	279	1095	14.5
12.00R24	8.50	20	S600	160/157K	4500	4125	315	1226	15
315/80R22.5	9.00	20	S600	156/150M	4000	3350	312	1076	14.5
295/80R22.5	9.00	18	S600	152/149M	3550	3250	292	1044	15.5

ON&OFF MIXED

PRODUCT MANUALS



D268

Position: Drive Position



- ✔ Suitable to drive position of truck on rough road.
- ✔ Wide tread and open shoulder blocks help enhance traction and braking on rough roads with mud or gravel.
- ✔ Special tread compounds resist chipping, chunking and tearing

Size	RIM	P.R.	Pattern	L./S.R.	Max load(kg)		S.W.	O.D.	T.D.
	inch				Single	Dual			
11R22.5	8.25	18	D268	149/146M	3250	3000	268	1054	20
12R22.5	9.00	18	D268	152/149K	3550	3250	292	1086	18
315/80R22.5	9.00	20	D268	156/150K	4000	3350	312	1076	20



D608

Position: Drive Position



- ✔ Strong carcass design for better load-bearing.
- ✔ High-density carcass material to enhance the bearing capacity of the bead.
- ✔ Tread groove bottom stone discharge structure design, improve the self-cleaning ability of tires, prolong the usage life under mixed road conditions.

Size	RIM	P.R.	Pattern	L./S.R.	Max load(kg)		S.W.	O.D.	T.D.
	inch				Single	Dual			
11.00R20	8.00	18	D608	152/149K	3550	3250	293	1085	18.5
12.00R20	8.50	20	D608	156/153K	4000	3650	309	1121	19.5



D688

Position: Drive Position



- ✔ Wide tread and open shoulder blocks help enhance traction and braking on rough roads with mud or gravel.
- ✔ Wide and depth pattern design with low heat generating formula provides good turning stability.
- ✔ Outstanding self-cleaning tread design ensures long-life service in ON/OFF road conditions.

Size	RIM	P.R.	Pattern	L./S.R.	Max load(kg)		S.W.	O.D.	T.D.
	inch				Single	Dual			
7.00R16LT	5.50F	14	D688	118/114K	1320	1180	202	776	14
7.50R16	6.00G	14	D688	122/118K	1500	1320	215	806	16
8.25R16	6.50H	16	D688	128/124K	1800	1600	225	854	14.5
8.25R20	6.50	16	D688	139/137J	2430	2300	234	974	17
9.00R20	7.00	16	D688	144/142K	2800	2650	260	1025	18
10.00R20	7.50	18	D688	149/146K	3250	3000	278	1054	18
11.00R20	8.00	18	D688	152/149K	3550	3250	288	1084	18.5
12.00R20	8.50	20	D688	156/153J	4000	3650	309	1121	19.5
12.00R24	8.50	20	D688	160/157K	4500	4125	316	1222	19.5



D802

Position: Drive Position



- ✔ Maximized traction in soft soil and mud through massive, open lateral shoulder grooves.
- ✔ Aggressive direction tread with robust tread blocks providing extra traction for on&off road condition.
- ✔ Special rubber compound ensuring more resistance to cuts and tearing.

Size	RIM	P.R.	Pattern	L./S.R.	Max load(kg)		S.W.	O.D.	T.D.
	inch				Single	Dual			
11R22.5	8.25	18	D802	149/146M	3250	3000	268	1054	20
12R22.5	9.00	18	D802	152/149K	3550	3250	296	1086	20
13R22.5	9.75	20	D802	156/150K	4000	3350	320	1124	20
295/80R22.5	9.00	18	D802	152/149L	3550	3250	292	1045	20
315/80R22.5	9.00	20	D802	156/150K	4000	3350	312	1076	20



D803

Position: Drive Position



- Special pattern design provides good traction and driving capacity.
- Tough belt for smooth tread wear and longer mileage.
- Special compound for high resistance against tread cut.

Size	RIM	P.R.	Pattern	L.I./S.R.	Max load(kg)		S.W.	O.D.	T.D.
	inch				Single	Dual			
10.00R20	7.50	18	D803	149/146K	3250	3000	278	1054	18



D807 PREMIUM

Position: Drive Position



- Large pattern and lateral fold grooves provide excellent driving and braking capability.
- Guiding pattern design for better driving and handling performance.
- The groove bottom reinforcement design effectively increases the circumferential rigidity of the pattern.

Size	RIM	P.R.	Pattern	L.I./S.R.	Max load(kg)		S.W.	O.D.	T.D.
	inch				Single	Dual			
11R22.5	8.25	18	D807	149/146M	3250	3000	268	1058	22
215/75R17.5	6.00	18	D807	135/133J	2180	2060	210	766	15
235/75R17.5	6.75	18	D807	143/141J	2725	2575	230	795	15.5
295/80R22.5	9.00	18	D807	152/149L	3550	3250	292	1049	22



D805

Position: Drive Position



- Drive axle tire applicable for mud and sand terrain with short on high-way use.
- Wide tread and open shoulder blocks help enhance traction and braking on rough roads with mud or gravel.
- Special tread compounds resist chipping, chunking and tearing.

Size	RIM	P.R.	Pattern	L.I./S.R.	Max load(kg)		S.W.	O.D.	T.D.
	inch				Single	Dual			
315/80R22.5	9.00	20	D805	156/150K	4000	3350	312	1076	18



D820 PREMIUM

Position: Drive Position



- Rugged directional tread design helps boost traction and improves handling and durability.
- Wear resistant and tear resistant tread compound for long tread life in mixed road conditions.
- The latest rigid skeleton materials ensures the stability of the tire carcass after tire inflation, suppresses deformation, resist irregular wear and extend tire life.

Size	RIM	P.R.	Pattern	L.I./S.R.	Max load(kg)		S.W.	O.D.	T.D.
	inch				Single	Dual			
295/80R22.5	9.00	18	D820	154/151K	3750	3450	292	1049	22



D876

PREMIUM

Position: Drive Position



- Wear resistant and tear resistant tread compound for long tread life in mixed road conditions.
- Stone ejector and tie bar protect belts.
- The transverse grooves provide excellent traction, and the strong frame material and ring structure provide super load-carrying capacity.

Size	RIM	P.R.	Pattern	L.I/S.R.	Max load(kg)		S.W.	O.D.	T.D.
	inch				Single	Dual			
295/80R22.5	9.00	18	D876	154/151K	3750	3450	292	1049	22



D900

Position: Drive Position



- Special rubber compound designed for varied applications.
- Reinforced crown ply to improve resistance against oxidation. broad, directional block tread.
- Good mileage potential, Excellent resistance to damage and punctures on/off road with longer wear life and service life.

Size	RIM	P.R.	Pattern	L.I/S.R.	Max load(kg)		S.W.	O.D.	T.D.
	inch				Single	Dual			
12.00R24	8.50	20	D900	160/157K	4500	4125	315	1226	16



D878

PREMIUM

Position: Drive Position



- wider tread and super-wear-resistant carbon black formula provide excellent wear-resistant performance.
- The 3D steel sipe technology provide excellent traction and braking performance.
- The latest rigid skeleton materials ensures the stability of the tire carcass after tire inflation, suppresses deformation, resist irregular wear and extend tire life.

Size	RIM	P.R.	Pattern	L.I/S.R.	Max load(kg)		S.W.	O.D.	T.D.
	inch				Single	Dual			
11R22.5	8.25	18	D878	149/146M	3250	3000	279	1065	25.5



T306

PREMIUM

Position: ALL Position



- Zigzag groove geometry minimizes stone retention, protecting belts.
- Wear resistant and tear resistant tread compound for long tread life in mixed road conditions.
- Open shoulder tread design provides excellent traction, resists irregular wear and reduces heat.

Size	RIM	P.R.	Pattern	L.I/S.R.	Max load(kg)		S.W.	O.D.	T.D.
	inch				Single	Dual			
11R22.5	8.25	18	T306	149/146M	3250	3000	279	1047	16.5
295/80R22.5	9.00	18	T306	154/151M	3750	3450	292	1038	16.5



T605

Position: ALL Position



- Reinforced bead and body to strengthen the puncture resistance tear resistance.
- Suitable for mixed road conditions and relatively poor road condition.
- Open groove and bottom design given excellent self-cleaning performance.

Size	RIM	P.R.	Pattern	L.I/S.R.	Max load(kg)		S.W. mm	O.D. mm	T.D. mm
	inch				Single	Dual			
385/55R22.5	12.25	20	T605	160L	4500	4500	383	999	17
385/65R22.5	11.75	20	T605	160L	4500	4500	389	1074	17
425/65R22.5	12.25	22	T605	166K	5300	—	355	1149	18
445/65R22.5	13.00	20	T605	169K	5800	—	454	1149	18



T609

Position: ALL Position



- Optimized carcass construction for better durability.
- High-intensity casing carcass materials for reinforcing bead and loading capacity.
- Offset block shoulder design with SILICA compound promotes good traction and abrasion resistance.

Size	RIM	P.R.	Pattern	L.I/S.R.	Max load(kg)		S.W. mm	O.D. mm	T.D. mm
	inch				Single	Dual			
9.00R20	7.00	16	T609	144/142K	2800	2650	260	1018	15.5
10.00R20	7.50	18	T609	149/146K	3250	3000	278	1051	16.5
11.00R20	8.00	18	T609	152/149K	3550	3250	288	1079	16
12.00R20	8.50	20	T609	156/153K	4000	3650	309	1115	16.5
12R22.5	9.00	18	T609	152/149K	3550	3250	296	1078	16
315/80R22.5	9.00	20	T609	156/150M	4000	3350	308	1070	14.5





MINING

PRODUCT MANUALS



D800

Position: Drive Position



- Deep tread with stone drilling protectors to promote traction and floatation capacity on rough roads.
- Latest technology carcass materials for reinforcing bead and loading capacity
- Special mining rubber compound for high resistance against tread cut.

Size	RIM	P.R.	Pattern	L.I/S.R.	Max load(kg)		S.W.	O.D.	T.D.
	inch				Single	Dual			
9.00R20	7.00	16	D800	144/142G	2800	2650	260	1027	20



D860

Position: Drive Position



- High-intensity casing carcass materials for reinforcing bead and loading capacity.
- Extra deep tread with stone drilling protectors to promote traction and long original mileage.
- Special rubber compound ensuring more resistance to cuts and tearing

Size	RIM	P.R.	Pattern	L.I/S.R.	Max load(kg)		S.W.	O.D.	T.D.
	inch				Single	Dual			
9.5R17.5	6.75	18	D860	143/141 J	2725	2575	232	847	18
11R22.5	8.25	18	D860	149/146M	3250	3000	268	1054	20
12R22.5	9.00	18	D860	152/149K	3550	3250	300	1090	22
12R22.5	9.00	18	D860	152/149G	3550	3250	300	1090	22
13R22.5	9.75	20	D860	156/150K	4000	3350	320	1124	22
11.00R20	8.00	18	D860	152/149G	3550	3250	293	1085	21
12.00R20	8.50	20	D860	156/153G	4000	3650	309	1125	22
12.00R24	8.50	20	D860	160/157K	4500	4125	316	1227	22
295/80R22.5	9.00	18	D860	152/149K	3550	3250	292	1045	20
295/80R22.5	9.00	18	D860	152/149G	3550	3250	292	1045	20
315/80R22.5	9.00	20	D860	156/150K	4000	3350	308	1085	22
11R24.5	8.25	18	D860	152/149K	3550	3250	279	1106	20



D880

Position: Drive Position



- Extra deep tread with stone drilling protectors to promote traction and floatation capacity on rough roads.
- Latest technology carcass materials for reinforcing bead and loading capacity.
- Special rubber compound for high resistance against tread cut.

Size	RIM	P.R.	Pattern	L./S.R.	Max load(kg)		S.W.	O.D.	T.D.
	inch				Single	Dual			
8.25R16	6.50H	16	D880	128/124G	1800	1600	225	861	18
8.25R20	6.50	16	D880	139/137G	2430	2300	234	978	19
9.00R20	7.00	16	D880	144/142G	2800	2650	260	1027	20
10.00R20	7.50	18	D880	149/146G	3250	3000	276	1058	20
11.00R20	8.00	18	D880	152/149G	3550	3250	288	1094	23.8
12.00R20	8.50	20	D880	156/153G	4000	3650	309	1130	24



D818

PREMIUM

Position: Drive Position



- Extra deep tread with stone drilling protectors to promote traction and floatation capacity on rough roads.
- Latest technology carcass materials for reinforcing bead and loading capacity.
- Special rubber compound for high resistance against tread cut.

Size	RIM	P.R.	Pattern	L./S.R.	Max load(kg)		S.W.	O.D.	T.D.
	inch				Single	Dual			
11R22.5	8.25	18	D818	149/146K	3250	3000	220	1060	23