



PRODUCT GUIDE
TRUCK & BUS TIRE

A high-angle photograph of a lush green mountain valley. A winding asphalt road curves through the forested hillsides. A white truck with two green trailers is driving on the road. In the background, majestic mountains rise, some with patches of snow and partially shrouded in mist. The sky is filled with soft, white clouds. The overall scene is vibrant and natural.

GREENLANDER

FOR GREEN LAND TIRE

**PRODUCT GUIDE
TRUCK & BUS TIRE**

 **HIGHWAY** 01-12

 **ON & OFF** 13-24

 **MINING** 25-26



01-02 FT100 · FT101 · FT102 · AA106



AD109 · AA112



03-04 AA116 · AA117 · FT118 · AA121



AA122 · AD123 · FT126 · AA128



05-06 FT129 · AA130 · AD131



FT132 · FT133 · TT136 · FT138



07-08 FT151 · FT152 · AD153 · FT156



AA161 · FT162+ · FT162



09-10 TT166 · FT167 · FT168 · AT169



FT172 · AA173 · AA176 · DT177



11-12 AD181 · AA182 · AD183



AA192 · AA197 · AA198



13-14 AD603 · AD605 · AD607 · AA609



AD610 · AD613 · AD615 · AD616



15-16 DT618 · AD625 · AD626 · AD627



DT633 · DD635 · AD638



17-18 AD650 · AD651 · AD653 · AD656



AD657 · AD658 · DT663 · DT665



19-20 AD667 · AD668 · AD669



AD671 · AD673 · AD675 · AD676



21-22 AD677 · DD678



AD682 · AD683 · AD685 · AD686



23-24 AD687 · DT688 · AD693 · AD695



DT699



25-26 AD809 · AD858 · AD866 · AD885



AD886 · AD888 · AD893 · AD899





01-02

FT100 · FT101 · FT102 · AA106
AD109 · AA112

03-04

AA116 · AA117 · FT118 · AA121
AA122 · AD123 · FT126 · AA128

05-06

FT129 · AA130 · AD131
FT132 · FT133 · TT136 · FT138

07-08

FT151 · FT152 · AD153 · FT156
AA161 · FT162+ · FT162

09-10

TT166 · FT167 · FT168 · AT169
FT172 · AA173 · AA176 · DT177

11-12

AD181 · AA182 · AD183
AA192 · AA197 · AA198



HIGHWAY



FT100



STEER AND TRAILER POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
295/60R22.5	18	9.00	3350	3075	150	147	K	246	915	900	130	15	-



AD109



ALL POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
11R22.5	18	8.25	3150	2900	148	145	M	220	1052	850	125	22	-



FT101



STEER AND TRAILER POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
12R22.5	18	9.00	3550	3250	152	149	K	247	1077	930	135	17	-



AA112



ALL POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
11R22.5	18	8.25	3150	2900	148	145	M	216	1046	850	125	14	276
11R24.5	16	8.25	3250	3000	149	146	M	216	1097	830	120	14	254
215/75R17.5	18	6.00	1700	1600	135	133	J	175	768	860	125	13	600
225/70R19.5	14	6.75	1800	1700	128	126	M	181	814	760	110	13	522
235/75R17.5	18	6.75	2725	2575	143	141	J	192	793	900	130	12.5	505
245/70R19.5	16	7.50	2240	2120	136	134	M	201	841	825	120	13	-
255/70R22.5	16	7.50	2500	2300	140	137	M	194	926	800	116	14	-
265/70R19.5	18	7.50	2725	2575	143	141	J	213	869	850	124	13	430
275/70R22.5	18	8.25	3150	2900	148	145	M	216	952	900	130	14	316
285/75R24.5	16	8.25	3000	2725	146	143	M	220	1047	830	120	14	260
295/75R22.5	16	9.00	3000	2725	146	143	M	226	1009	830	120	14	290



FT102



STEER AND TRAILER POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
12R22.5	18	9.00	3550	3250	152	149	K	230	1074	930	135	16	-



AA106



ALL POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
12R22.5	18	9.00	3550	3250	152	149	K	230	1074	930	135	16	-



* New Developing Sizes / The Labeling Information are Subject to Change Without Notice

AA116



ALL POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
12R22.5	18	9.00	3550	3250	152	149	K	236	1077	930	135	17	-

AA122



ALL POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
11R22.5	18	8.25	3000	2725	146	143	M	210	1060	830	120	21	276
11R24.5	16	8.25	3250	3000	149	146	M	210	1111	830	120	21	254
285/75R24.5	16	8.25	3000	2725	146	143	M	216	1061	830	120	21	260
295/75R22.5	16	9.00	3000	2725	146	143	M	218	1023	830	120	21	290

AA117



ALL POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
12R22.5	18	9.00	3550	3250	152	149	K	214	1074	930	135	17	-

AD123



ALL POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
11R22.5	16	8.25	3000	2725	146	143	M	210	1037	830	120	15	-
11R22.5	18	8.25	3150	2900	148	145	M	210	1037	850	125	15	-
12R22.5	18	9.00	3550	3250	152	149	M	215	-	930	135	15	-
13R22.5	20	9.75	4000	3650	156	150	L	238	-	930	135	15	-
315/80R22.5	20	9.00	4000	3350	156	150	M	235	1062	850	125	15	-

FT118



STEER AND TRAILER POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
315/80R22.5	20	9.00	4000	3350	156	150	L	260	1077	850	125	16	218

FT126



STEER AND TRAILER POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
11R22.5	18	8.25	3150	2900	148	145	M	210	-	850	125	15	-
295/80R22.5	18	9.00	3550	3250	152	149	M	235	1031	900	130	15	-
315/80R22.5	20	9.00	4000	3350	156	150	M	220/225	1062	850	125	15	-
385/55R22.5	20	12.25	4500	-	160	158	L	300	-	900	130	15	-
385/65R22.5	20	11.75	4500	-	160	-	L	296	1058	900	130	15	-

AA121



ALL POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
275/70R22.5	18	8.25	3150	2900	148	145	K	242	955	900	130	22	-

AA128



ALL POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
12R22.5	18	9.00	3550	3250	152	149	K	236/246	1077	930	135	17	-

FT129



STEER AND TRAILER POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
12R22.5	18	9.00	3550	3250	152	149	K	242	1078	930	135	17	-

FT132



STEER AND TRAILER POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
295/60R22.5	18	9.00	3350	3075	150	147	K	246	915	900	130	15	-

AA130



ALL POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
12R22.5	18	9.00	3550	3250	152	149	K	242	1080	930	135	18	-

FT133



STEER AND TRAILER POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
295/80R22.5	18	9.00	3550	3250	152	149	L	250	1039	900	130	17	-
295/80R22.5	18	9.00	3550	3250	152	149	M	250	1039	900	130	17	-

AD131



ALL POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
12R22.5	18	9.00	3550	3250	152	149	K	242	1084	930	135	20	-

TT136



TRAILER POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
11R24.5	16	8.25	3250	3000	149	146	M	204	1091	830	120	11	-
285/75R24.5	16	8.25	3000	2725	146	143	M	208	1041	830	120	11	-
295/75R22.5	16	9.00	3000	2725	146	143	M	210	1003	830	120	11	-

FT138



STEER AND TRAILER POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
385/65R22.5	20	11.75	4500	-	160	-	L	296	1058	900	130	15	-
385/55R22.5	20	12.25	4500	-	160	158	L	300	-	900	130	15	-



* New Developing Sizes / The Labeling Information are Subject to Change Without Notice



FT151



STEER AND TRAILER POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
245/70R19.5	18	7.50	2800	2650	144	142	J	219	841	900	130	15	-



AA161



ALL POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
11R22.5	16	8.25	3000	2725	146	143	M	216	1053	830	120	16	-
12R22.5	18	9.00	3550	3250	152	149	M	228	1075	930	135	18	240
13R22.5	18	9.75	3750	3450	154	151	M	240	1122	830	120	20	226
295/80R22.5	18	9.00	3550	3250	152	149	M	222	1046	900	130	18	260
315/80R22.5	20	9.00	4000	3350	156	150	M	232	1081	850	125	18	-



FT152



STEER AND TRAILER POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
12R22.5	18	9.00	3550	3250	152	149	K	232/240	1073	930	135	15	-



FT162+



STEER AND TRAILER POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
12R22.5	18	9.00	3550	3250	152	149	M	214	1071	930	135	16	-



AD153



ALL POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
245/70R19.5	18	7.50	2800	2650	144	142	J	222	844	900	130	16	-



FT156



STEER AND TRAILER POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
12R22.5	18	9.00	3550	3250	152	149	K	230	1074	930	135	17	-



FT162



STEER AND TRAILER POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
11R22.5	16	8.25	3000	2725	146	143	M	202	1048	830	120	15	276
12R22.5	18	9.00	3550	3250	152	149	M	228	1072	930	135	17	240
275/80R22.5	16	8.25	3250	3000	149	146	M	215	1010	850	125	14	290
295/60R22.5	18	9.00	3350	3075	150	147	M	224	915	900	130	15	-
295/80R22.5	18	9.00	3550	3250	152	149	M	235	1041	900	130	15	254
315/80R22.5	20	9.00	4000	3350	156	150	M	245	1077	850	125	16	240



TT166



TRAILER POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
385/65R22.5	20	11.75	4500	-	160	-	K	284	1064	900	130	15	198
425/65R22.5	20	12.25	5150	-	165	-	K	318	1118	825	120	15	-
445/65R22.5	20	13.00	5800	-	169	-	K	351	1144	900	130	15	-



FT172



STEER AND TRAILER POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
315/80R22.5	20	9.00	4000	3350	156	150	M	240	1068	850	125	15	240



FT167



STEER AND TRAILER POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
11R22.5	16	8.25	3000	2725	146	143	M	210	1037	830	120	15	-
11R22.5	18	8.25	3150	2900	148	145	M	210	1037	850	125	15	-
12R22.5	18	9.00	3550	3250	152	149	M	215	-	930	135	15	-
295/80R22.5	18	9.00	3550	3250	152	149	M	235	1031	900	130	15	-
315/80R22.5	20	9.00	4000	3350	156	150	M	235	1062	850	125	15	-



AA173



ALL POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
12R22.5	18	9.00	3550	3250	152	149	L	230	1078	930	135	19	-



FT168



STEER AND TRAILER POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
12R22.5	18	9.00	3550	3250	152	149	K	247	1077	930	135	17	-



AA176



ALL POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
12R22.5	12	9.00	2725	2575	143	141	K	214	1074	620	90	17	-
12R22.5	18	9.00	2725	2575	152	149	K	214	1074	620	90	17	-



AT169



ALL POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
385/55R22.5	20	12.25	4500	-	160	158	L	300	-	900	130	15	-
385/65R22.5	20	11.75	4500	-	160	-	L	290	-	900	130	15	-



DT177



DRIVE AND TRAILER POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
425/65R22.5	20	12.25	5150	-	165	-	J	318	1124	825	120	18	-
445/65R22.5	20	13.00	5800	-	169	-	K	351	1150	900	130	18	-



AD181



ALL POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
10.00R20	18	7.50	3250	3000	149	146	L	204	1049	930	135	17	280
11.00R20	18	8.0	3550	3250	152	149	L	211	1083	930	135	17	260
11R22.5	18	8.25	3150	2900	148	145	M	216	1048	850	125	15	276
11R24.5	16	8.25	3250	3000	149	146	M	208	1099	830	120	15	250
12.00R20	20	8.50	4000	3650	156	153	L	240	1119	900	130	17	228
12.00R24	20	8.50	4500	4125	160	157	K	226/234	1218	900	130	18	196
12R22.5	18	9.00	3550	3250	152	149	M	225	1071	930	135	16	-
12R24.5	18	9.00	3750	3450	154	151	K	212	1126	930	135	16	220
13R22.5	20	9.75	4000	3650	156	153	L	239/226	1116	930	135	17	226
265/70R19.5	18	7.50	2725	2575	143	141	M	213	874	850	124	15	430
315/80R22.5	20	9.00	4000	3350	156	150	M	225	1077	850	125	15	240
325/95R24	22	9.0	4750	4500	162	160	K	226/234	1218	930	135	18	196
6.50R16LT	12	5.50F	1060	925	110	105	M	138	747	670	100	10	810
7.00R16LT	14	5.50F	1320	1180	118	114	M	148	773	770	110	11	640
7.50R16LT	14	6.00G	1500	1320	122	118	L	150/158	801	770	110	13	600
8.25R16LT	16	6.50H	1800	1600	128	124	L	168	850	770	110	13	530
9.00R20	16	7.0	2800	2650	144	142	L	185	1018	900	130	16	300



AA192



ALL POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
11R22.5	16	8.25	3000	2725	148	145	J	236	1060	830	120	21	-



AA197



ALL POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
12.00R24	20	8.50	4500	4125	160	157	K	237	1223	900	130	15	196



AA182



ALL POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
12.00R24	20	8.50	4500	4125	160	157	K	222	1212	900	130	15	196
325/95R24	22	9.00	4750	4500	162	160	K	238	1215	850	125	16	-



AD183



ALL POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
11.00R20	18	8.0	3550	3250	152	149	L	224	1082	930	135	17	-
12.00R20	20	8.50	4000	3650	156	153	L	240	1122	900	130	18	-



AA198



ALL POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
12.00R24	20	8.50	4500	4125	160	157	K	230	1214	900	130	16	196
325/95R24	22	9.0	4750	4500	162	160	K	230	1214	930	135	16	-



GRENLANDER

13-14

AD603 · AD605 · AD607 · AA609
AD610 · AD613 · AD615 · AD616

15-16

DT618 · AD625 · AD626 · AD627
DT633 · DD635 · AD638

17-18

AD650 · AD651 · AD653 · AD656
AD657 · AD658 · DT663 · DT665

19-20

AD667 · AD668 · AD669
AD671 · AD673 · AD675 · AD676

21-22

AD677 · DD678
AD682 · AD683 · AD685 · AD686

23-24

AD687 · DT688 · AD693 · AD695
DT699



ON & OFF

AD603



ALL POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
11.00R20	18	8.0	3550	3250	152	149	K	224	1085	930	135	16	-
12.00R20	20	8.50	4000	3650	156	153	K	230	1118	900	130	16	-
325/95R24	22	9.00	4750	4500	162	160	K	238	1215	850	125	16	-

AD610



ALL POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
12.00R20	20	8.50	4000	3650	156	153	L	240	1121	900	130	17	-

AD605



ALL POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
11.00R20	18	8.0	3550	3250	152	149	K	235	1084	930	135	19	-
12.00R20	20	8.50	4000	3650	156	153	K	238	1121	900	130	18	-

AD613



ALL POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
11R22.5	18	8.25	3150	2900	149	146	J	226	1054	850	125	23	-

AD607



DRIVE AND TRAILER POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
12R22.5	18	9.00	3550	3250	152	149	K	235	1079	930	135	19	-

AD615



ALL POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
11.00R20	18	8.00	3550	3250	152	149	K	230	1086	930	135	20	-
12.00R20	20	8.50	4000	3650	156	153	K	238	1124	900	130	20	-

AA609



ALL POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
11.00R20	18	8.0	3550	3250	152	149	L	228	1080	930	135	17	-
12.00R20	20	8.50	4000	3650	156	153	L	240	1121	900	130	17	-

AD616



ALL POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
12R22.5	18	9.00	3550	3250	152	149	K	240	1084	930	135	20	-

DT618



DRIVE AND TRAILER POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
12R22.5	18	9.00	3550	3250	152	149	K	253	1092	930	135	20	-

DT633



DRIVE AND TRAILER POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
295/80R22.5	18	9.00	3550	3250	152	149	L	256	1050	900	130	22	-

AD625



ALL POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
12R22.5	18	9.00	3550	3250	152	149	J	235	1079	930	135	19	-

DD635



DRIVE POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
12.00R20	20	8.50	4000	3650	156	153	L	240	1121	900	130	18	-

AD626



ALL POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
12R22.5	18	9.00	3550	3250	152	149	J	235	1085	930	135	22	-

AD638



DRIVE POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
11.00R20	18	8.00	3550	3250	152	149	L	230	1087	930	135	18	-
12.00R20	20	8.50	4000	3650	156	153	k	240	1121	900	130	18	-

AD627



ALL POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
11.00R20	18	8.0	3550	3250	152	149	L	228	1087	930	135	19	-
12.00R20	20	8.50	4000	3650	156	153	K	240	1121	900	130	18	-
13R22.5	20	9.75	4000	3650	156	153	F	245	1128	930	135	21	-



AD650



DRIVE POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
12.00R20	20	8.50	4000	3650	156	153	k	226	1116	900	130	15	-

AD657



ALL POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
11.00R20	18	8.0	3550	3250	152	149	F	240	1121	930	135	21	-
11.00R20	18	8.0	3550	3250	152	149	F	240	1092	930	135	21	-
12.00R20	20	8.50	4000	3650	156	153	F	250	1124	900	130	21	-

AD651



DRIVE POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
11.00R20	18	8.00	3550	3250	152	149	L	228	1080	930	135	17	-
12.00R20	20	8.50	4000	3650	156	153	K	236	1118	900	130	16	-
13R22.5	18	9.75	3750	3450	154	151	K	232	1118	830	120	17	-

AD658



ALL POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
11.00R20	18	8.00	3550	3250	152	149	K	235	1085	930	135	19	260
12.00R20	20	8.50	4000	3650	156	153	K	243	1122	900	130	19	220

AD653



ALL POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
10.00R20	18	7.50	3250	3000	149	146	L	212/218	1054	930	135	17	-
12.00R20	20	8.50	4000	3650	156	153	L	238	1118	900	130	16	-
13R22.5	18	9.75	3750	3450	154	151	L	238/232	1118	830	120	17	-

DT663



DRIVE AND TRAILER POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
12R22.5	18	9.00	3550	3250	152	149	M	228	1077	930	135	19	240

AD656



ALL POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
315/70R22.5	20	9.00	3750	3350	154	150	L	248	1020	900	131	20	-

DT665



DRIVE AND TRAILER POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
12R22.5	18	9.00	3550	3250	152	149	M	238	1090	930	135	22	240

AD667



ALL POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
12.00R20	20	8.50	4000	3650	156	153	F	252	1125	900	130	21	-

AD671



ALL POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
12R22.5	18	9.00	3550	3250	152	149	K	240	1084	930	135	23	-



AD668

ALL POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
11.00R20	18	8.0	3550	3250	152	149	K	235	1084	930	135	19	-
11.00R20	18	8.0	3550	3250	152	149	K	235	1084	930	135	18	-
12.00R20	20	8.50	4000	3650	156	153	K	243	1121	900	130	19	-
12.00R20	20	8.50	4000	3650	156	153	K	238	1121	900	130	18	-
12R22.5	18	9.00	3550	3250	152	149	K	235	1084	930	135	18	-
13R22.5	18	9.75	3750	3450	154	151	K	238	1121	830	120	18	-
13R22.5	18	9.75	3750	3450	154	151	L	238	1121	830	120	18	220

AD673



ALL POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
235/75R17.5	18	6.75	2725	2575	143	141	J	192	793	900	130	16.5	-
315/80R22.5	22	9.00	6000	5450	158	156	J	256	1089	970	140	22	-
325/95R24	22	9.00	4750	4500	162	160	K	240	1231	850	125	24	-

AD675



ALL POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
11R22.5	16	8.25	3000	2725	146	143	K	220	1054	830	120	19	-
12R22.5	18	9.00	3550	3250	152	149	J	242	1088	930	135	22	-

AD669



ALL POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
12.00R20	20	8.50	4000	3650	156	153	K	240	1119	900	130	19	208
13R22.5	20	9.75	4000	3650	156	153	F	245	1128	930	135	21	-

AD676



ALL POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
11R22.5	18	8.25	3150	2900	148	145	J	220	1058	850	125	25	-
295/80R22.5	18	9.00	3550	3250	152	149	J	250	1051	900	130	23	-

AD677



ALL POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		

12R22.5	18	9.00	3550	3250	152	149	K	260	1096	930	135	22	-
---------	----	------	------	------	-----	-----	---	-----	------	-----	-----	----	---

DD678



DRIVE POSITONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		

11.00R20	18	8.0	3550	3250	152	149	L	1087	230	930	135	18	-
11R22.5	18	8.25	3150	2900	148	145	M	1058	216	850	125	20	276
12R22.5	18	9.00	3550	3250	152	149	M	1079	230	930	135	20	-
215/75R17.5	18	6.00	1700	1600	135	133	J	773	175	860	125	15	600
225/70R19.5	14	6.75	1800	1700	128	126	M	819	181	760	110	15	522
235/75R17.5	18	6.75	2725	2575	143	141	J	793	192	900	130	14.5	505
245/70R19.5	16	7.50	2240	2120	136	134	M	846	201	825	120	15	-
265/70R19.5	18	7.50	2725	2575	143	141	J	874	213	850	124	15	430
275/80R22.5	16	8.25	3250	3000	149	146	M	1019	225	850	125	19	290
285/70R19.5	18	8.25	3350	3150	150	148	J	894	220	900	130	16	380
295/80R22.5	18	9.00	3550	3250	152	149	M	1051	235	900	130	20	254
315/80R22.5	20	9.00	4000	3350	156	150	M	1085	245	850	125	20	240



AD682



ALL POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		

7.50R16LT	14	6.00G	1500	1320	122	118	L	170	806	770	110	16	600
8.25R16LT	16	6.50H	1800	1600	128	124	L	184	856	770	110	16	530
10.00R20	18	7.50	3250	3000	149	146	L	218	1052	930	135	18	280
11.00R20	18	8.0	3550	3250	152	149	L	230	1087	930	135	18	260
12.00R20	20	8.50	4000	3650	156	153	L	240	1123	900	130	19	228

AD683



ALL POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		

11R22.5	16	8.25	3000	2725	146	143	M	210	1048	830	120	20	-
11R22.5	18	8.25	3150	2900	148	145	M	210	1048	850	125	20	-

AD685



ALL POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		

12.00R20	20	8.50	4000	3650	156	153	K	238	1119	900	130	16	-
----------	----	------	------	------	-----	-----	---	-----	------	-----	-----	----	---

AD686



ALL POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		

11R22.5	18	8.25	3150	2900	148	145	M	210	1048	850	125	20	-
12R22.5	18	9.00	3550	3250	152	149	M	230	-	930	135	20	-
295/80R22.5	18	9.00	3550	3250	152	149	L	240	1041	900	130	20	-
315/80R22.5	20	9.00	4000	3350	156	150	L	240	1072	850	125	20	-



AD687



ALL POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
13R22.5	20	9.75	4000	3650	156	150	K	240	-	930	135	20	-
295/80R22.5	18	9.00	3550	3250	152	149	K	240	1041	900	130	20	-
315/80R22.5	20	9.00	4000	3350	156	150	K	240	1072	850	125	20	-



DT699



DRIVE AND TRAILER POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
315/80R22.5	20	9.00	4000	3350	156	150	L	268	1089	850	125	22	218



DT688



DRIVE AND TRAILER POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
315/80R22.5	20	9.00	4000	3350	156	150	M	266	1087	850	125	21	218



AD693



ALL POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
13R22.5	20	9.75	4000	3650	156	153	L	244	1118	930	135	18	-



AD695



ALL POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
325/95R24	22	9.00	4750	4500	162	160	K	240	1231	850	125	20	-





25-26

AD809 · AD858 · AD866 · AD885
AD886 · AD888 · AD893 · AD899



MINING



AD809



ALL POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
11.00R20	18	8.0	3550	3250	152	149	F	228	1092	930	135	23	-
12.00R20	20	8.50	4000	3650	156	153	F	238	1130	900	130	24	-



AD886



ALL POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
11.00R20	18	8.0	3550	3250	152	149	E	224	1098	930	135	25	238
12.00R20	20	8.50	4000	3650	156	153	E	240	1132	900	130	26	208



AD858



ALL POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
11.00R20	18	8.0	3550	3250	152	149	F	222	1095	900	130	23	-
12.00R20	20	8.50	4000	3650	156	153	F	238	1130	930	135	24	-



AD888



ALL POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
12.00R20	20	8.50	4000	3650	156	153	E	240	1132	900	130	26	-



AD866



ALL POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
12.00R20	20	8.50	4000	3650	156	153	F	250	1132	900	130	26	-



AD893



ALL POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
11.00R20	18	8.0	3550	3250	152	149	F	241	1098	930	135	25	-
12.00R20	20	8.50	4000	3650	156	153	F	250	1132	900	130	26	-



AD885



ALL POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
11.00R20	18	8.0	3550	3250	152	149	E	222	1095	930	135	23	238
12.00R20	20	8.50	4000	3650	156	153	E	238	1129	900	130	24	208



AD899



ALL POSITIONS

Size	Ply Rating	Rim	Max load(kg)		Load Index		Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual	S	D		SW(mm)	OD(mm)	kPa	psi		
12.00R20	20	8.50	4000	3650	156	153	F	250	1132	900	130	26	-